

SAFETY DATA SHEET

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier Mineral Spirits

Other means of identification

Product code ADV 124-1
Recommended use Solvent

Manufacturer/Importer/Supplier/Distributor information

Company name INTERNATIONAL AUTOBODY MARKETING GROUP

Address 1505 NORTH HAYDEN RD, SUITE 111

SCOTTSDALE, AZ 85257

UNITED STATES

Website www.advantagerefinish.com

Telephone 1-87-REFINISH

480.451.4451

Emergency phone number 800-424-9300 ChemTrec EMERGENCY 24 Hrs.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids Category 3

Skin irritation Category 2

Eye irritation Category 2A

Germ cell mutagenicity Category 1B

Carcinogenicity Category 1B

Specific target organ tox-

icity - single exposure

Category 3 (Central nervous system)

Aspiration hazard Category 1

GHS Label element

Hazard pictograms







Signal word

Hazard statements	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H340 May cause genetic defects. H350 May cause cancer.
Precautionary statements	Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray. P264 Wash skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ eye protection/ face protection. P281 Use personal protective equipment as required. Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P331 Do NOT induce vomiting. P332 + P313 If skin irritation occurs: Get medical advice/ attention. P337 + P313 If skin irritation persists: Get medical

advice/ attention.

Danger

P362 Take off contaminated clothing and wash before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Potential Health Effects

Primary Routes of Entry

Inhalation Skin contact Eye Contact Ingestion

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this ma-

terial: Kidney Liver Skin

Respiratory disorders Central nervous system

auditory system

Symptoms of Overexposure

Irritation Dermatitis Headache Dizziness

Unconsciousness

Aspiration may cause pulmonary oedema and pneu-

monitis. Fatigue Nausea

Carcinogenicity:

IARC

Group 1: Carcinogenic to humans

71-43-2 **Benzene

Group 2B: Possibly carcinogenic to humans

91-20-3 **Naphthalene

98-82-8 **Cumene

100-41-4 **Ethylbenzene

ACGIH Confirmed human carcinogen

71-43-2 **Benzene

Confirmed animal carcinogen with unknown relevance to

humans

100-41-4 **Ethylbenzene

OSHA OSHA specifically regulated carcinogen

71-43-2 **Benzene

NTP Known to be human carcinogen

71-43-2 **Benzene

Reasonably anticipated to be a human carcinogen

91-20-3 **Naphthalene

Emergency Overview

Imagency overtical	
Appearance	liquid
Colour	clear, transparent
Odour	petroleum distillates, solvent-like, hydrocarbon-like
Hazard Summary	No information available.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

CAS-No.	Chemical Name	Concentration (%)
8052-41-3 /	Stoddard Solvent AND/OR Solvent Naphtha	90 - 100
64742-88-7 /	(Petroleum), Medium Aliph. AND/OR Hy-	
64742-48-9	drotreated Naphtha, Heavy	
25551-13-7	**Benzene, trimethyl-	5 - 10
95-63-6	**1,2,4-trimethylbenzene	5 - 10
1330-20-7	**Mixed Xylenes	5 - 10
91-20-3	**Naphthalene	5 - 10
111-84-2	**Nonane	5 - 10

108-88-3	**Toluene	1 - 5
98-82-8	**Cumene	1 - 5
100-41-4	**Ethylbenzene	1 - 5
110-54-3	**n-Hexane	1 - 5
71-43-2	**Benzene	0.1 - 1

Special Notes:

** Other substances in the product which may pre-

sent a health or environmental hazard.

SECTION 4. FIRST AID MEASURES

General advice Move out of dangerous area.

Show this safety data sheet to the doctor in attend-

ance.

Symptoms of poisoning may appear several hours

later.

Do not leave the victim unattended.

medical advice.

Remove to fresh air. Give artificial respiration if not breathing. Keep victim warm and at rest. Call a phy-

sician.

If on skin, rinse well with water.

Wash contaminated clothing before reuse. Thoroughly clean shoes before reuse.

In case of eye contact Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed Keep respiratory tract clear.

Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious per-

son.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed

Irritation Dermatitis Headache Dizziness

Unconsciousness

Aspiration may cause pulmonary oedema and pneu-

monitis. Fatigue Nausea

Protection of first-aiders First Aid responders should pay attention to self-

protection and use the recommended protective cloth-

ing

Notes to physician In case of shortness of breath, give oxygen.

Treat symptomatically

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing

media

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains

or water courses.

Hazardous combustion

products

Carbon oxides

Fume Smoke

Unburned hydrocarbons

Specific extinguishing

methods

Use a water spray to cool fully closed containers.

Further information Collect contaminated fire extinguishing water sepa-

rately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local requ-

lations.

For safety reasons in case of fire, cans should be

stored separately in closed containments.

Special protective equip-

ment for firefighters

Wear full firefighting turn-out gear (full Bunker gear),

and respiratory protection (SCBA).

NFPA Flammable and Combustible Liquids Classification:

Flammable Liquid Class IC

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains

inform respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with noncombustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regula-

tions (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling

Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before

use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in

the application area.

Take precautionary measures against static discharg-

es.

Provide sufficient air exchange and/or exhaust in work

rooms.

Open drum carefully as content may be under pres-

sure.

Dispose of rinse water in accordance with local and

national regulations.

Conditions for safe storage

No smoking.

Keep container tightly closed in a dry and well-

ventilated place.

Containers which are opened must be carefully re-

sealed and kept upright to prevent leakage.

Observe label precautions.

Electrical installations / working materials must com-

ply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

CAS-No. Components Value type (Form of exposure) Stoddard Solvent AND/OR 64742-88-7 / 64742-48- 9 TWA TWA TWA TWA TWA TWA TWA T
Solvent Naphtha (Petrole-um), Medium Aliph. AND/OR Hydrotreated Naphtha, Heavy TWA 350 mg/m3 NIOSH RI C 1,800 mg/m3 NIOSH RI TWA 500 ppm OSHA Z-12,900 mg/m3 OSHA Z-12,900 mg/m3 OSHA PO 525 mg/m3 ACGIH
C 1,800 mg/m3 NIOSH RI TWA 500 ppm OSHA Z-: 2,900 mg/m3 TWA 100 ppm OSHA P0 525 mg/m3 25551-13-7 **Benzene, trimethyl- TWA 25 ppm ACGIH
TWA 500 ppm OSHA Z-1 2,900 mg/m3 TWA 100 ppm OSHA P0 525 mg/m3 25551-13-7 **Benzene, trimethyl- TWA 25 ppm ACGIH
2,900 mg/m3 TWA 100 ppm OSHA P0 525 mg/m3 25551-13-7 **Benzene, trimethyl- TWA 25 ppm ACGIH
525 mg/m3 25551-13-7 **Benzene, trimethyl- TWA 25 ppm ACGIH
TWA 25 ppm OSHA P0 125 mg/m3
95-63-6 **1,2,4-trimethylbenzene TWA 25 ppm NIOSH RI
1330-20-7 **Mixed Xylenes TWA 100 ppm 435 mg/m3 OSHA Z-1
TWA 100 ppm ACGIH
STEL 150 ppm ACGIH
STEL 150 ppm OSHA P0 655 mg/m3
TWA 100 ppm OSHA P0 435 mg/m3
91-20-3 **Naphthalene TWA 10 ppm ACGIH
STEL 15 ppm ACGIH
TWA 10 ppm NIOSH RI 50 mg/m3
ST 15 ppm NIOSH RI 75 mg/m3
TWA 10 ppm OSHA Z-1 50 mg/m3
TWA 10 ppm OSHA P0 50 mg/m3
STEL 15 ppm OSHA P0 75 mg/m3
111-84-2 **Nonane TWA 200 ppm ACGIH
TWA 200 ppm NIOSH RI 1,050 mg/m3
TWA 200 ppm OSHA PO

1		1	1,050 mg/m3	1
108-88-3	**Toluene	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm	OSHA Z-2
		TWA	100 ppm 375 mg/m3	OSHA PO
		STEL	150 ppm 560 mg/m3	OSHA PO
98-82-8	**Cumene	TWA	50 ppm	ACGIH
		TWA	50 ppm 245 mg/m3	NIOSH REL
		TWA	50 ppm 245 mg/m3	OSHA Z-1
		TWA	50 ppm 245 mg/m3	OSHA PO
100-41-4	**Ethylbenzene	TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm 545 mg/m3	NIOSH REL
		TWA	100 ppm 435 mg/m3	OSHA Z-1
		TWA	100 ppm 435 mg/m3	OSHA PO
		STEL	125 ppm 545 mg/m3	OSHA PO
110-54-3	**n-Hexane	TWA	50 ppm	ACGIH
		TWA	50 ppm 180 mg/m3	NIOSH REL
		TWA	500 ppm 1,800 mg/m3	OSHA Z-1
		TWA	50 ppm 180 mg/m3	OSHA PO
71-43-2	**Benzene	TWA	0.5 ppm	ACGIH
		STEL	2.5 ppm	ACGIH
		TWA	0.1 ppm	NIOSH REL
		ST	1 ppm	NIOSH REL
		PEL	1 ppm	OSHA CARC
		STEL	5 ppm	OSHA CARC
		TWA	10 ppm	OSHA Z-2
		CEIL	25 ppm	OSHA Z-2
		Peak	50 ppm	OSHA Z-2

Biological occupational exposure limits

Company			Dialasiasi	C	D	D:-
Components	CAS-No.	Control parame- ters	Biological specimen	Sam- pling time	Permissi- ble con- centration	Basis
**Mixed Xylenes	1330- 20-7	Methylhip puric acids	Urine	End of shift (As soon as possible after expo- sure ceases)	1.5 g/g creatinine	ACGIH BEI
**Toluene	108-88-	Toluene	In blood	Prior to last shift of work- week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after expo- sure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after expo- sure ceases)	0.3 mg/g Creatinine	ACGIH BEI
**Ethylbenzene	100-41- 4	Sum of mandelic acid and phenyl glyoxylic acid	Urine	End of shift at end of work- week	0.7 g/g creatinine	ACGIH BEI
**n-Hexane	110-54- 3	2,5- Hexanedi- one	Urine	End of shift at end of work- week	0.4 mg/l	ACGIH BEI
**Benzene	71-43-2	S- Phenyl- mercap-	Urine	End of shift (As	25 µg/g creatinine	ACGIH BEI

turic acid		soon as possible after expo- sure ceases)		
t,t- Muconic acid	Urine	End of shift (As soon as possible after expo- sure ceases)	500 µg/g creatinine	ACGIH BEI

Personal protective equipment

Respiratory protection No personal respiratory protective equipment normally

required.

In the case of vapour formation use a respirator with

an approved filter.

Hand protection

Remarks The suitability for a specific workplace should be dis-

cussed with the producers of the protective gloves.

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal pro-

cessing problems.

Skin and body protection impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work

place.

Hygiene measures When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance liquid

Colour clear, transparent

Odour petroleum distillates, solvent-like, hydrocarbon-like

Odour Threshold No data available

pH not applicable

Freezing Point (Freezing -76 °C (-105 °F)

Point)

Boiling Point (Boiling 157 - 218 °C (315 - 424 °F) point/boiling range)

Flash point 37.78 - 44 °C (100.00 - 111 °F)

Evaporation rate 0.14 - 0.2 n-Butyl Acetate

Flammability (solid, gas)

No data available

Burning rate No data available

Upper explosion limit 5.6 - 7.0 %(V)

Lower explosion limit 0.5 - 1.1 %(V)

Vapour pressure 0.22 - 0.62 mmHg @ 20 °C (68 °F)

Relative vapour density 4.9

Relative density 0.77 - 0.80 @ 15.5 °C (59.9 °F)

Reference substance: (water = 1)

Density No data available

Bulk density No data available

Solubility(ies)

Water solubility 0.05 g/l negligible

Solubility in other sol- No data available

vents

Partition coefficient: n- No data available

octanol/water

Auto-ignition temperature 229 - 282 °C

Thermal decomposition No data available

Viscosity

Viscosity, kinematic 1.03 mm2/s @ 40 °C (104 °F)

Regulatory VOC (lbs/gal) 6.44

Regulatory VOC (g/l) 772.00

Actual VOC (lbs/gal) 6.44

Actual VOC (g/l) 772.00

SECTION 10. STABILITY AND REACTIVITY

Reactivity No dangerous reaction known under conditions of

normal use.

Chemical stability Stable under normal conditions.

Possibility of hazardous

reactions

No hazards to be specially mentioned.

Conditions to avoid Keep away from heat, flame, sparks and other ignition

sources.

Incompatible materials Reducing agents

Strong bases

Strong oxidizing agents

Hazardous decomposition

products

Carbon monoxide, carbon dioxide and unburned hy-

drocarbons (smoke).

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Components:

8052-41-3 / 64742-88-7 / 64742-48-9:

Acute oral toxicity LD50 (rat): > 5,000 mg/kg

Assessment: The substance or mixture has no acute

oral toxicity

Acute inhalation toxicity LC50 (rat, male and female): >5500

Exposure time: 4 h

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity LD50 (rabbit, male and female): > 2,000 mg/kg

GLP: yes

Assessment: The substance or mixture has no acute

dermal toxicity

Skin corrosion/irritation

Product:

Classification: Irritating to skin.

Components:

8052-41-3 / 64742-88-7 / 64742-48-9:

Species: rabbit Exposure time: 4 h

Method: OECD Test Guideline 404

Result: Irritating to skin.

Serious eye damage/eye irritation

Product:

Classification: Irritating to eyes.

Components:

8052-41-3 / 64742-88-7 / 64742-48-9:

Species: rabbit

Result: Irritating to eyes.

Method: OECD Test Guideline 405

Respiratory or skin sensitisation

Components:

8052-41-3 / 64742-88-7 / 64742-48-9:

Test Type: Buehler Test Species: guinea pig

Method: OECD Test Guideline 406

Result: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Components:

8052-41-3 / 64742-88-7 / 64742-48-9:

Genotoxicity in vitro Test Type: Ames test

Metabolic activation: with and without metabolic acti-

vation

Result: positive

Test Type: Chromosome aberration test in vitro

Test species: mouse lymphoma cells

Metabolic activation: with and without metabolic acti-

vation

Result: positive

Genotoxicity in vivo Test Type: In vivo micronucleus test

Test species: mouse

Cell type: Peripheral blood erythrocytes

Application Route: Inhalation Exposure time: 3 mths Dose: 138 - 2200 mg/m3

Result: positive

Test Type: In vivo micronucleus test

Test species: rat

Cell type: Peripheral blood erythrocytes

Application Route: Inhalation Exposure time: 3 mths Dose: 138 - 2200 mg/m3

Result: positive

Germ cell mutagenicity-

Assessment

Positive result(s) from in vivo heritable germ cell mu-

tagenicity tests in mammals

Carcinogenicity

Components:

8052-41-3 / 64742-88-7 / 64742-48-9:

Species: rat, (male and female) Application Route: Inhalation Exposure time: 105 wks

Activity duration: 6 h

Dose: 0, 138, 550, 1100, 2200 mg/m3 Frequency of Treatment: 5 days/week

NOAEL: 138 mg/m³

Result: No evidence of carcinogenic activity in females, Evidence of carcinogenic

activity in males

Symptoms: Increased incidence of pheochromocytomas in adrenal glands

Remarks: Category 1B

Carcinogenicity - As-

sessment

Possible human carcinogen

98-82-8:

Carcinogenicity - As-

sessment

Not classifiable as a human carcinogen.

100-41-4:

Carcinogenicity - As-

sessment

Not classifiable as a human carcinogen.

Reproductive toxicity

Components:

8052-41-3 / 64742-88-7 / 64742-48-9:

Effects on fertility

Species: rat

Application Route: Oral

Dose: 0, 750, 1500, 3000 mg/kg/d

General Toxicity - Parent: NOAEL: 1,500 mg/kg body

weight

Fertility: NOAEL: >= 3,000 mg/kg body weight

Symptoms: weight loss

Result: No reproductive effects.

Remarks: Information given is based on data obtained

from similar substances.

Species: rat

Application Route: Oral

Dose: 0, 325, 750, 1500 mg/kg/d

General Toxicity - Parent: NOAEL: 750 mg/kg body

weight

General Toxicity F1: NOAEL: 750 mg/kg body weight Fertility: NOAEL: >= 1,500 mg/kg body weight Symptoms: Reduced maternal body weight gain. Re-

duced offspring weight gain.

Result: Animal testing did not show any effects on

fertility.

Remarks: Information given is based on data obtained

from similar substances.

Species: rat

Application Route: Dermal Dose: 0, 165, 330, 494 mg/kg

General Toxicity - Parent: NOAEL: >= 494 mg/kg

Fertility: NOAEL: >= 494 mg/kg

Early Embryonic Development: NOAEL: >= 494

mg/kg

Result: No reproductive effects.

Remarks: Information given is based on data obtained

from similar substances.

Effects on foetal development

Species: rat

Application Route: Oral

Dose: 0, 500, 1000, 1500, 2000 milligram per kilo-

aram

Duration of Single Treatment: 10 d

General Toxicity Maternal: NOAEL: 500 mg/kg body

weight

Teratogenicity: NOAEL: 2,000 mg/kg body weight Developmental Toxicity: NOAEL: 1,000 mg/kg body

weight

Symptoms: Reduced body weight Method: OECD Test Guideline 414

Result: Developmental toxicity occurred at maternal

toxicity dose levels, No teratogenic effects.

Reproductive toxicity - Assessment

No evidence of adverse effects on sexual function and fertility, and on development, based on animal exper-

iments.

No evidence of adverse effects on sexual function and fertility, and on development, based on animal exper-

iments.

STOT - single exposure

Product:No data available

Components:

8052-41-3 / 64742-88-7 / 64742-48-9:

Exposure routes:	Target Organs:	Assessment:	Remarks:
Inhalation	Central nervous system	May cause drowsiness or dizziness., The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.	

25551-13-7:No data available

95-63-6:No data available

1330-20-7: No data available

91-20-3:No data available

111-84-2:No data available

108-88-3:No data available

98-82-8: No data available

100-41-4: No data available

110-54-3:No data available

71-43-2: No data available

STOT - repeated exposure

Product:No data available

Components:

8052-41-3 / 64742-88-7 / 64742-48-9: No data available

25551-13-7: No data available

95-63-6:No data available

1330-20-7: No data available

91-20-3:No data available

111-84-2: No data available

108-88-3: No data available

98-82-8:No data available

100-41-4:No data available

110-54-3:No data available

71-43-2:No data available

Repeated dose toxicity

Components:

8052-41-3 / 64742-88-7 / 64742-48-9:

Species: rat, male and female

NOAEL: 275

Application Route: Inhalation Exposure time: 14 wks

Number of exposures: 6 h/d, 5 d/wk

Dose: 138, 275, 550, 1100, 2200mg/m3

Group: yes

Symptoms: nasal symptoms, Testicular effects, Kidney disorders Remarks: male rat hydrocarbon nephropathy not relevant to humans

Species: rat, male LOAEL: 750 mg/kg Application Route: Oral Exposure time: 70 - 90 d Number of exposures: Daily

Dose: 0, 750, 1500, 3000 mg/kg/day

GLP: yes

Symptoms: weight loss, Local irritation

Species: mouse, male and female

LOAEL: 138

Application Route: Inhalation Exposure time: 14 wks

Number of exposures: 6 h/d, 5 d/wk

Dose: 138, 275, 550, 1100, 2200mg/m3

Group: yes

Symptoms: Spleen effects

Species: rat, female NOAEL: 750 mg/kg Application Route: Oral Exposure time: 21 wks Number of exposures: Daily

Dose: 0, 325, 750, 1500 mg/kg/day

GLP: yes

Symptoms: weight loss, Local irritation

Species: rat, male and female

NOAEL: >= 24

Application Route: Inhalation Test atmosphere: vapour Exposure time: 4 wks

Number of exposures: 6 h/d, 5 d/wk

Dose: 0, 24 mg/m3

GLP: yes

Remarks: Information given is based on data obtained from similar substances.

Species: rat, male and female

NOAEL: >= 0.5 mg/l Application Route: Dermal Exposure time: 4 wks

Number of exposures: 6 h/d, 5 d/wk Dose: 0, 1.01, 0.05, 0.5 ml/kg/day Method: OECD Test Guideline 410

GLP: yes

Remarks: Information given is based on data obtained from similar substances.

Repeated dose toxicity - : Causes skin irritation.

Assessment

Aspiration toxicity

Components:

8052-41-3 / 64742-88-7 / 64742-48-9:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

8052-41-3 / 64742-88-7 / 64742-48-9:

Toxicity to fish LL50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l

Exposure time: 96 h
Test Type: semi-static test
Analytical monitoring: yes

Method: OECD Test Guideline 203

GLP: yes

Remarks: Information given is based on data obtained

from similar substances.

Toxicity to daphnia and

other aquatic inverte-

brates

EL50 (Daphnia magna (Water flea)): 1.4 mg/l

Exposure time: 48 h Test Type: static test Analytical monitoring: yes

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae EL50 (Pseudokirchneriella subcapitata): 1 mg/l

End point: Growth rate Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

GLP: yes

Remarks: Information given is based on data obtained

from similar substances.

Ecotoxicology Assessment

Acute aquatic toxicity Toxic to aquatic life.

Chronic aquatic toxicity Toxic to aquatic life with long lasting effects.

Persistence and degradability

Components:

8052-41-3 / 64742-88-7 / 64742-48-9:

Biodegradability aerobic

> Concentration: 101 mg/l Biodegradation: 61 % Testing period: 10 d Exposure time: 28 d Lag phase: 5 d

Test substance: Solvent naphtha (petroleum), heavy

aromatic GLP: yes

Bioaccumulative potential

Components:

95-63-6:

Partition coefficient: n-

octanol/water

Remarks: No data available

1330-20-7:

Partition coefficient: n-

octanol/water

log Pow: 2.77 - 3.15

91-20-3:

Partition coefficient: n-

octanol/water

log Pow: 3.4 (25 °C)

pH: 7 - 7.5

108-88-3:

Partition coefficient: n-

octanol/water

log Pow: 2.73

98-82-8:

Partition coefficient: n-

octanol/water

log Pow: 3.55 (23 °C)

71-43-2:

Partition coefficient: n-

octanol/water

Pow: 2.13 (25 °C)

pH: 7

Mobility in soil

Components:

8052-41-3 / 64742-88-7 / 64742-48-9:

Stability in soil : Remarks: Adsorbs on soil.

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection

of Stratospheric Ozone - CAA Section 602 Class I Sub-

stances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological in-

formation

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to

aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

Dispose of in accordance with all applicable local,

state and federal regulations.

Dispose of as unused product.

Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty

drum.

SECTION 14. TRANSPORT INFORMATION

IATA (International Air Transport Association): UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III, Flash Point:37.78 - 44 °C(100.00 - 111 °F)

IMDG (International Maritime Dangerous Goods): UN1268, PETROLEUM DISTILLATES, N.O.S., 3, III, Marine Pollutant (STODDARD SOLVENT, TRIMETHYLBENZENE)

DOT (Department of Transportation): UN1268, PETROLEUM DISTILLATES, N.O.S., CBL, III

Special Notes: The flash point for this material is greater than 100 F

(38 C). Therefore, in accordance with 49 CFR 173.150(f) non-bulk containers (<450L or <119 gallon capacity) of this material may be shipped as non-regulated when transported solely by land, as long as the material is not a hazardous waste, a marine pollutant, or specifically listed as a hazardous substance.

SECTION 15. REGULATORY INFORMATION

OSHA Hazards Flammable liquid, Carcinogen, Moderate skin irritant,

Moderate eye irritant, Moderate respiratory irritant, Teratogen, Reproductive hazard, Mutagen, Aspiration

hazard

WHMIS Classification B2: Flammable liquid

D2A: Very Toxic Material Causing Other Toxic Effects D2B: Toxic Material Causing Other Toxic Effects

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
**Benzene	71-43-2	10	1000

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Fire Hazard

Hazards Chronic Health Hazard
Acute Health Hazard

Acute nearth nazaru

SARA 302 SARA 302: No chemicals in this material are subject

to the reporting requirements of SARA Title III,

Section 302.

SARA 313 The following components are subject to reporting

levels established by SARA Title III, Section 313:

95-63-6 **1,2,4- 5.14 %

trimethylbenzene

1330-20-7 **Mixed Xylenes 5 %

91-20-3	** N aphthalene	5 %
108-88-3	**Toluene	1.1 %
98-82-8	**Cumene	1 %
100-41-4	**Eth y lbenzene	1 %
110-54-3	**n-Hexane	1 %
71-43-2	**Benzene	0.9999 %

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

1330-20-7	**Mixed Xylenes	5 %
91-20-3	**Naphthalene	5 %
108-88-3	**Toluene	1.1 %
98-82-8	**Cumene	1 %
100-41-4	**Ethylbenzene	1 %
110-54-3	**n-Hexane	1 %
71-43-2	**Benzene	0.9999 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F). The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

1330-20-7	**Mixed Xylenes	5 %
108-88-3	**Toluene	1.1 %
98-82-8	**Cumene	1 %
100-41-4	**Ethylbenzene	1 %
71-43-2	**Benzene	0.9999 %

Clean Water Act

This product contains the following toxic pollutants listed under the U.S. Clean Water Act Section 307

91-20-3 **Naphthalene		5 %
108-88-3	**Toluene	1.1 %
100-41-4	**Eth y lbenzene	1 %

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

1330-20-7	**Mixed Xylenes	5 %
91-20-3	**Naphthalene	5 %
108-88-3	**Toluene	1.1 %
100-41-4	**Ethylbenzene	1 %
71-43-2	**Benzene	0.9999 %

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

1330-20-7	**Mixed Xylenes	5 %
91-20-3 **Naphthalene		5 %
108-88-3	**Toluene	1.1 %

	-41-4 13-2	**Eth **Ber	ylbenzene nzene	1 % 0.9999 %	
Massachuset	ts Riaht T	o Kno	ow		
	8052-41-3 64742-88 64742-48	3 / -7 /	Stoddard Solvent AND/OR Sol Naphtha (Petroleum), Medium AND/OR Hydrotreated Naphth Heavy	n Aliph.	90 - 100 %
	25551-13	-7	**Benzene, trimethyl-		5 - 10 %
	95-63-6		**1,2,4-trimethylbenzene		5 - 10 %
	1330-20-7	7	**Mixed Xylenes		5 - 10 %
	91-20-3		**Naphthalene		5 - 10 %
	111-84-2		**Nonane		5 - 10 %
	108-88-3		**Toluene		1 - 5 %
	98-82-8		**Cumene		1 - 5 %
	100-41-4		**Ethylbenzene		1 - 5 %
	110-54-3		**n-Hexane		1 - 5 %
	71-43-2		**Benzene		0.1 - 1 %
Pennsylvania	a Right To	Knov	v		
	8052-41-3 64742-88 64742-48 25551-13 95-63-6 1330-20-7 91-20-3	-7 / -9 , -7	Stoddard Solvent AND/OR Solv Naphtha (Petroleum), Medium AND/OR Hydrotreated Naphtha Heavy **Benzene, trimethyl- **1,2,4-trimethylbenzene **Mixed Xylenes **Naphthalene	Aliph.	90 - 100 % 5 - 10 % 5 - 10 % 5 - 10 % 5 - 10 %
	111-84-2		**Nonane		5 - 10 %
	108-88-3		**Toluene		1 - 5 %
	98-82-8		**Cumene		1 - 5 %
	100-41-4		**Eth y lbenzene		1 - 5 %
	110-54-3		**n-Hexane		1 - 5 %
	71-43-2	;	**Benzene		0.1 - 1 %
New Jersey I			Staddard Calvant AND/OD Cal	.aat	00 100 %
	8052-41-3 64742-88 64742-48	-7 / -9	Stoddard Solvent AND/OR Solv Naphtha (Petroleum), Medium AND/OR Hydrotreated Naphtha Heavy	Aliph.	90 - 100 %
	25551-13		**Benzene, trimeth y l-		5 - 10 %
	95-63-6		**1,2,4-trimethylbenzene		5 - 10 %
	1330-20-7		**Mixed Xylenes		5 - 10 %
	91-20-3		**Naphthalene		5 - 10 %
	111-84-2		**Nonane		5 - 10 %
	108-88-3		**Toluene		1 - 5 %
	98-82-8		**Cumene		1 - 5 %

	100-41-4	**Ethylbenzene	1 - 5 %	
	110-54-3	**n-Hexane	1 - 5 %	
	71-43-2	**Benzene	0.1 - 1 %	
California Prop 65		WARNING! This product contains a ch the State of California to cause cance		
	91-20-3	**Naphthalene	:I .	
	98-82-8	**Cumene		
100-41-4 71-43-2		**Ethylbenzene		
		**Benzene		
		WARNING: This product contains a ch	nemical known to	
		the State of California to cause birth	defects or other	
		reproductive harm.		
	108-88-3	**Toluene		
	71-43-2	**Benzene		

The components of this product are reported in the following inventories:


United States TSCA Inventory	y (positive listing) (On TSCA Invento- ry)
Canadian Domestic Substances List (DSL)	y (positive listing) (All components of this product are on the Canadian DSL.)
Australia Inventory of Chemical Substances (AICS)	y (positive listing) (On the inventory, or in compliance with the inventory)
New Zealand. Inventory of Chemical Substances	y (positive listing) (On the inventory, or in compliance with the inventory)
Japan. ENCS - Existing and New Chemical Substances Inventory	n (Negative listing) (Not in compliance with the inventory)
Korea. Korean Existing Chemicals Inventory (KECI)	y (positive listing) (On the inventory, or in compliance with the inventory)
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	y (positive listing) (On the inventory, or in compliance with the inventory)

China. Inventory of Existing Chemical Substances in China (IECSC)	y (positive listing) (On the inventory,
	or in compliance with the inventory)

SECTION 16. OTHER INFORMATION

Version 2.1

Revision Date 06/19/2019



Our Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Legecy MSDS: R0000589

Material number:

782184, 675948, 640758, 581940, 554166, 554247, 554201, 554165, 86611, 547091, 547061, 547062, 550245, 508581, 70142, 102366, 102354, 70154, 69933, 102904, 87262, 102901, 157504, 503757, 39830, 20077, 20075, 86037, 722819, 20072, 16056759, 16056758, 102692, 70151, 102993, 20084, 20082, 16075682, 16002525, 765097, 687316, 661358, 85984, 69595, 20078, 102913, 20076, 502847

ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%	
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level	
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency	
NDSL	Canada, Non-Domestic Sub- stances List	NIOSH	National Institute for Occupational Safety & Health	
CNS	Central Nervous System	NTP	National Toxicology Program	
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals	
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level	
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration	
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration	
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit	
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philipines Inventory of Commercial Chemical Substances	
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic	
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act	
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit	
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.	
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value	
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average	
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act	
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Compositon, Complex Reaction Products, and Biological Materials	
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System	
LC50		Lethal Concentration 50%		