ADVANTAGE REFINSH PRODUCTS TECHNICAL DATA INFORMATION

DATED: JUNE 2014

PRODUCTS:

191-01	Waterborne Surface Cleaner	Gallon

PRODUCT DESCRIPTION:

ADVANTAGE #191 is a special waterborne blend for removing wax, grease, silicone, oils and other contaminants from surfaces to be painted. This fast drying product leaves no residue making it the perfect pre-paint low VOC surface cleaner.

DIRECTIONS FOR USE:

#191 should be used before and after sanding a repair area. For best performance, compressed air should be used to eliminate excess sanding dust from the repair area before using ADVANTAGE Waterborne Surface Cleaner.

- 1. Apply a liberal amount of #191 to a clean dry lint free cloth, saturating it. Have a second clean, dry cloth available before proceeding.
- 2. Wipe surface in one direction with saturated cloth. Clean 2 x 2 area at a time, changing cloths frequently to prevent surface contaminants.
- 3. Immediately wipe surface dry with a clean dry cloth while surface is still wet.
- 4. Remove excess #191 with a clean cloth soaked in clean water. Wipe dry with a clean, dry cloth.

Note: Do not use #191 on plastic or fiberglass parts. Application on these surfaces can generate static build-up, which can result in flash fire. Do not use #191 on soluble materials, like lacquer primers or topcoats.

TECHNICAL DATA:

CONTAINS: Acetone

REGULATORY VOC: 1.49 lbs/gal (179 g/L)
ACTUAL VOC: 0.00 lbs/gal (0.00 g/L)

CAS#: 67-64-1

FOR PROFESSIONAL USE ONLY Read MSDS Before Use

WARNING: KEEP AWAY FROM HEAT, SPARKS, FLAME AND SOURCES OF STATIC ELECTRICITY. USE WITH ADEQUATE VENTILATION. OPEN CONTAINER SLOWLY TO RELIEVE ANY PRESSURE. WHEN TRANSFERRING, USE PROPER BONDING AND GROUNDING PROCEDURES. DO NOT TASTE OR SWALLOW. MAY BE FATAL OR CAUSE BLINDNESS IF SWALLOWED. VAPOR

HARMFUL. DO NOT TRANSFER INTO UNMARKED CONTAINERS. KEEP OUT OF REACH OF CHILDREN.

SEE MSDS AND PRODUCT LABELS FOR ADDITIONAL SAFETY INFORMATION.

WWW.ADVANTAGEREFINISH.COM