



# SAFETY DATA SHEET

Revision date 15-Jun-2017

Version 5

Supersedes Date: 10-Jun-2017

## Section 1: PRODUCT AND COMPANY IDENTIFICATION

**Product Name** S/E HARDENER  
**Product Code** AD-20308.C01  
**UN/ID no** UN1263  
**Recommended Use** Paint, Coatings

### Details of the supplier of the safety data sheet

See section 16 for more information

ADVANTAGE REFINISH PRODUCTS  
a division of IAMG/International Autobody Marketing Group  
1505 N. Hayden Road  
Suite 111  
Scottsdale, AZ 85257  
www.AdvantageRefinish.com  
1-87REFINISH

ADVANTAGE REFINISH PRODUCTS  
a division of IAMG/International Autobody Marketing Group  
1368 United Blvd.  
Unit 102  
Coquitlam, BC V3K 6Y2  
www.AdvantageRefinish.com  
1-87REFINISH

**E-mail address** [No information available](#)

**Emergency telephone number** Chemtrec: 800-424-9300

## Section 2: HAZARDS IDENTIFICATION

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 1B
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 2

### Label elements



**Signal word**

**DANGER**

#### **HAZARD STATEMENTS**

Highly flammable liquid and vapor  
Causes skin irritation  
Causes serious eye irritation  
May cause allergy or asthma symptoms or breathing difficulties if inhaled  
May cause an allergic skin reaction  
May cause cancer  
Suspected of damaging fertility or the unborn child  
May cause damage to organs through prolonged or repeated exposure  
May be fatal if swallowed and enters airways  
May cause drowsiness or dizziness  
May cause respiratory irritation

#### **PREVENTION**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. In case of inadequate ventilation wear respiratory protection. Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### **RESPONSE**

IF exposed or concerned: Get medical advice/attention.

##### **Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

##### **Skin**

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

##### **Inhalation**

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

##### **Ingestion**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

##### **Fire**

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction.

#### **STORAGE**

Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

#### **DISPOSAL**

Dispose of contents/containers in accordance with local regulations.

#### **OTHER HAZARDS**

Not applicable.

#### **UNKNOWN ACUTE TOXICITY**

.0001% of the mixture consists of ingredient(s) of unknown toxicity.

### **Section 3: COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical Name	CAS No	weight-%
Isophoronediiisocyanate, Homopolymer	53880-05-0	30 - 35
Toluene	108-88-3	20 - <25
Xylenes	1330-20-7	15 - <20
Ethylbenzene	100-41-4	3 - <5
n-Butyl acetate	123-86-4	3 - <5
Solvent naphtha, petroleum, light aromatic	64742-95-6	3 - <5
Benzene, 1,2,4-trimethyl-	95-63-6	3 - <5
Isophorone diisocyanate	4098-71-9	0.3 - <1
Cumene	98-82-8	0.3 - <1

## Section 4: FIRST AID MEASURES

### First Aid Measures

#### General advice

IF exposed or concerned: Get medical advice/attention

#### Eye contact

If eye irritation persists: Get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

#### Skin Contact

If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

#### Inhalation

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician IF INHALED: Remove person to fresh air and keep comfortable for breathing

#### Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do NOT induce vomiting

### Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

## Section 5: FIRE FIGHTING MEASURES

**Flammable properties** Flammable liquid.

**flash point** 39 °F / 4 °C

**Upper flammability limit:** No information available

**Lower flammability limit:** No information available

**Autoignition temperature** No information available

#### Explosion data

Sensitivity to Mechanical Impact No information available.  
Sensitivity to Static Discharge No information available.

#### Suitable extinguishing media

Dry chemical, CO2, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

**Hazardous combustion products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

**Specific hazards arising from the chemical**

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by inhalation. May cause sensitization by skin contact.

**Special protective equipment for fire-fighters**

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

## Section 6: ACCIDENTAL RELEASE MEASURES

**Personal precautions**

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

**Environmental precautions**

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

**Methods for containment**

Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up**

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

## Section 7: HANDLING AND STORAGE

**General advice**

Persons with a history of asthma, allergies, chronic or recurrent respiratory disease should not be exposed to any process in which this product is used. Examination of lung function should be carried out on a regular basis on persons spraying this product.

**Advice on safe handling**

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

**General Hygiene Considerations**

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

**Storage Conditions**

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**Exposure Guidelines**

**Exposure Limits**

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	Alberta	British Columbia	Ontario TWA	Quebec	OSHA PEL
---------------	-----------	---------	------------------	-------------	--------	----------

Toluene 108-88-3	TWA: 20 ppm	TWA: 50 ppm TWA: 188 mg/m <sup>3</sup> S*	TWA: 20 ppm Adverse reproductive effect	TWA: 20 ppm	TWA: 50 ppm TWA: 188 mg/m <sup>3</sup> S*	TWA: 200 ppm Ceiling: 300 ppm
Xylenes 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 150 ppm STEL: 651 mg/m <sup>3</sup>	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 150 ppm STEL: 651 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 125 ppm STEL: 543 mg/m <sup>3</sup>	TWA: 20 ppm	TWA: 20 ppm	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 125 ppm STEL: 543 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>
n-Butyl acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 713 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>	TWA: 20 ppm	TWA: 150 ppm STEL: 200 ppm	TWA: 150 ppm TWA: 713 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup>
Benzene, 1,2,4-trimethyl- 95-63-6	TWA: 25 ppm	TWA: 25 ppm TWA: 123 mg/m <sup>3</sup>	TWA: 25 ppm	TWA: 25 ppm	TWA: 25 ppm TWA: 123 mg/m <sup>3</sup>	
Isophorone diisocyanate 4098-71-9	TWA: 0.005 ppm	TWA: 0.005 ppm TWA: 0.05 mg/m <sup>3</sup>	TWA: 0.005 ppm Ceiling: 0.01 ppm Sensitizer	TWA: 0.005 ppm CEV: 0.02 ppm	TWA: 0.005 ppm TWA: 0.045 mg/m <sup>3</sup>	
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 246 mg/m <sup>3</sup>	TWA: 25 ppm STEL: 75 ppm	TWA: 50 ppm	TWA: 50 ppm TWA: 246 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 245 mg/m <sup>3</sup> S*

### Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

### Personal Protective Equipment

#### Eye/face protection

Tight sealing safety goggles.

#### Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

#### Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing. Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber.

#### Respiratory protection

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

#### Thermal Protection

No information available

### Environmental exposure controls

Do not allow into any sewer, on the ground or into any body of water. Local authorities should be advised if significant spillages cannot be contained.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state	liquid
Appearance	No information available
Odor	Solvent
Color	clear
Odor Threshold	No information available
pH value	No information available
Melting point/freezing point	No information available
Boiling point / boiling range	111 °C / 232 °F
flash point	4 °C / 39 °F

evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limit in Air	
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor Pressure	No information available
vapor density	No information available
Density (lbs per US gallon)	7.84
specific gravity	.94
Solubility(ies)	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available

#### Other information

### Section 10: STABILITY AND REACTIVITY

<b>Stability</b>	Stable under normal conditions.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Conditions to avoid</b>	Heat, flames and sparks.
<b>Hazardous Decomposition Products</b>	Carbon monoxide. Carbon dioxide (CO <sub>2</sub> ).
<b>Possibility of Hazardous Reactions</b>	None under normal processing.
<b>Hazardous polymerization</b>	None under normal processing.

### Section 11: TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

##### **Eye contact**

Causes serious eye irritation

##### **Skin Contact**

Causes skin irritation

May cause an allergic skin reaction

##### **Ingestion**

May be fatal if swallowed and enters airways

##### **Inhalation**

May cause drowsiness or dizziness

May cause respiratory irritation

#### Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Isophoronediiisocyanate, Homopolymer 53880-05-0	-	-	-
Toluene 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h
Xylenes 1330-20-7	= 3500 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit ) > 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h
n-Butyl acetate 123-86-4	= 10768 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 390 ppm ( Rat ) 4 h
Solvent naphtha, petroleum, light aromatic 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h

Benzene, 1,2,4-trimethyl- 95-63-6	= 3280 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 18 g/m <sup>3</sup> ( Rat ) 4 h
Isophorone diisocyanate 4098-71-9	= 1097 mg/kg ( Rat )	1060 - 4780 mg/kg ( Rabbit )	= 0.135 mg/L ( Rat ) 4 h
Cumene 98-82-8	= 1400 mg/kg ( Rat )	= 12300 µL/kg ( Rabbit )	> 3577 ppm ( Rat ) 6 h = 39000 mg/m <sup>3</sup> ( Rat ) 4 h

#### **Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (dermal) 5572 Mg/kg

ATEmix (inhalation-dust/mist) 5.3 mg/l

ATEmix (inhalation-vapor) 39 mg/l

**UNKNOWN ACUTE TOXICITY** .0001% of the mixture consists of ingredient(s) of unknown toxicity.

#### **Delayed and immediate effects as well as chronic effects from short and long-term exposure**

Chemical Name	ACGIH	IARC	NTP	OSHA
Ethylbenzene 100-41-4	A3	Group 2B		X
Cumene 98-82-8		Group 2B	Reasonably Anticipated	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen.

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans.

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present.

<b>Skin corrosion/irritation</b>	Causes skin irritation
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation
<b>Skin sensitization</b>	May cause an allergic skin reaction
<b>Respiratory sensitization</b>	May cause allergy or asthma symptoms or breathing difficulties if inhaled
<b>Germ cell mutagenicity</b>	Not applicable
<b>Carcinogenicity</b>	May cause cancer
<b>Reproductive Toxicity</b>	Suspected of damaging fertility or the unborn child
<b>Specific target organ toxicity (single exposure)</b>	May cause drowsiness or dizziness May cause respiratory irritation
<b>Specific target organ toxicity (repeated exposure)</b>	May cause damage to organs through prolonged or repeated exposure
<b>Aspiration hazard</b>	Not applicable

### **Section 12: ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

Environmental precautions Prevent product from entering drains.

#### **Persistence and degradability**

No information available

#### **Bioaccumulation**

No information available

#### **Mobility**

No information available

#### **Other adverse effects**

No information available

### **Section 13: DISPOSAL CONSIDERATIONS**

**Waste from residues/unused products**

Disposal should be in accordance with applicable regional, national and local laws and regulations

**Contaminated packaging**

Improper disposal or reuse of this container may be dangerous and illegal.

## Section 14: TRANSPORT INFORMATION

	<u>TDG</u>	<u>IMDG</u>	<u>IATA</u>
UN/ID no	UN1263	UN1263	UN1263
Proper shipping name	Paint	Paint	Paint
Hazard Class	3	3	3
Packing Group	II	II	II
Environmental hazard	Not applicable		
Special Provisions		163, 367 EmS-No F-E, S-E	A3, A72, A192

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

*The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.*

## Section 15: REGULATORY INFORMATION

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

All components are listed or exempt from listing

**DSL** - Canadian Domestic Substances List

All components are listed or exempt from listing

Chemical Name	Canada - NPRI (National Pollutant Release Inventory)
Toluene	Part 1, Group A Substance; Part 5, Individual Substances
Xylenes	Part 1, Group A Substance (total of all isomers of Xylene, including m-Xylene, CAS 108-38-3, o-Xylene, CAS 95-47-6, and p-Xylene, CAS 106-42-3); Part 5, Isomer Groups (total of all isomers of Xylene, including m-Xylene, CAS 108-38-3, o-Xylene, CAS 95-47-6, and p-Xylene, CAS 106-42-3)
Ethylbenzene	Part 1, Group A Substance
n-Butyl acetate	Part 5, Individual Substances
Solvent naphtha, petroleum, light aromatic	Part 5, Other Groups and Mixtures
Benzene, 1,2,4-trimethyl-	Part 1, Group A Substance; Part 5, Individual Substances
Isophorone diisocyanate	Part 1, Group A Substance
Cumene	Part 1, Group A Substance

## Section 16: OTHER INFORMATION

**HMIS**

**Health hazards** 3\*

\* = Chronic Health Hazard

**Flammability** 3

**Physical hazards** 0

**Personal Protection** X

**Prepared By**

Regulatory Department

**Revision date**

15-Jun-2017

**Revision Note**

No information available



**Disclaimer**

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

**End of Safety Data Sheet**