


**\* 1 Identification**

- **Product identifier**
- **Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics**
- **Article number: 3305, 3306, 3307**
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Manufactured for: IAMG International Autobody Marketing Group, 1505 North Hayden Road, Ste.111, Scottsdale, AZ 85257  
Information phone : 480.451.4451
- **Information department: 1-87-REFINISH**
- **Emergency telephone number: CHEMTREC 1-800-424-9300**

**\* 2 Hazard identification**

- **Classification of the substance or mixture**



Flammable Aerosols - Category 1

H222 Extremely flammable aerosol.



Gases Under Pressure - Compressed Gas

H280 Contains gas under pressure; may explode if heated.



Specific Target Organ Toxicity - Single Exposure - Category 2

H371 May cause damage to organs.



Eye Irritation - Category 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure - Category 3

H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

**Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics**

(Contd. of page 1)

· **Hazard pictograms**



· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Quartz (SiO<sub>2</sub>)  
acetone  
toluene  
titanium dioxide

· **Hazard statements**

H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H319 Causes serious eye irritation.  
H371 May cause damage to organs.  
H336 May cause drowsiness or dizziness.

· **Precautionary statements**


P210                      Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211                      Do not spray on an open flame or other ignition source.  
P251                      Do not pierce or burn, even after use.  
P260                      Do not breathe dust/fume/gas/mist/vapours/spray.  
P264                      Wash thoroughly after handling.  
P270                      Do not eat, drink or smoke when using this product.  
P280                      Wear protective gloves/protective clothing/eye protection/face protection.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P311              IF exposed or concerned: Call a poison center/doctor.  
P337+P313              If eye irritation persists: Get medical advice/attention.  
P405                      Store locked up.  
P410+P403              Protect from sunlight. Store in a well-ventilated place.  
P410+P412              Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501                      Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMS-ratings (scale 0 - 4)**



**Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics**

(Contd. of page 2)

### \* **3 Composition/Information on ingredients**

- **Chemical characterization: Mixtures**
- **Description:**  
*Mixture: consisting of the following components.*  
*Weight percentages*
- **Dangerous components: Void**

### \* **4 First aid measures**

- **Description of first aid measures**
- **After inhalation:** *Supply fresh air; consult doctor in case of complaints.*
- **After skin contact:** *Generally the product does not irritate the skin.*
- **After eye contact:**  
*Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.*
- **After swallowing:** *If symptoms persist consult doctor.*
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** *No further relevant information available.*
- **Indication of any immediate medical attention and special treatment needed**  
*No further relevant information available.*

### \* **5 Firefighting measures**

- **Extinguishing media**
- **Suitable extinguishing agents:**  
*CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.*
- **Special hazards arising from the substance or mixture**  
*During heating or in case of fire poisonous gases are produced.*
- **Advice for firefighters**
- **Protective equipment:**  
*Wear self-contained respiratory protective device.*  
*Mouth respiratory protective device.*

### \* **6 Accidental release measures**

- **Personal precautions, protective equipment and emergency procedures**  
*Mount respiratory protective device.*  
*Wear protective equipment. Keep unprotected persons away.*
- **Environmental precautions:** *Do not allow to enter sewers/ surface or ground water.*
- **Methods and material for containment and cleaning up:**  
*Dispose contaminated material as waste according to item 13.*  
*Ensure adequate ventilation.*
- **Reference to other sections**  
*See Section 7 for information on safe handling.*  
*See Section 8 for information on personal protection equipment.*  
*See Section 13 for disposal information.*

CA  
(Contd. on page 4)

**Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics**

(Contd. of page 3)

## \* 7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

· **Information about protection against explosions and fires:**

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurized containers.

· **Information about storage in one common storage facility:** Store away from oxidizing agents.

· **Further information about storage conditions:** Keep receptacle tightly sealed.

· **Specific end use(s)** No further relevant information available.

## \* 8 Exposure controls/ Personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

CA

**Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics**

(Contd. of page 4)

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses



Tightly sealed goggles

## \* 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Aerosol

Color:

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Not determined.

· **Change in condition**

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

55 °C

· **Flash point:**

-103 °C

· **Flammability (solid, gaseous):**

Not applicable.

· **Ignition temperature:**

405 °C

· **Decomposition temperature:**

Not determined.

· **Auto igniting:**

Product is not selfigniting.

· **Danger of explosion:**

In use, may form flammable/explosive vapour-air mixture.

· **Explosion limits:**

Lower:

1.1 Vol %

Upper:

13 Vol %

· **Vapor pressure at 20 °C:**

233 hPa

· **Density at 20 °C:**

0.8163 g/cm<sup>3</sup>

· **Relative density**

Not determined.

· **Vapor density**

Not determined.

· **Evaporation rate**

Not applicable.

(Contd. on page 6)

CA

**Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics**

(Contd. of page 5)

- **Solubility in / Miscibility with Water:** *Not miscible or difficult to mix.*
- **Partition coefficient (n-octanol/water):** *Not determined.*
- **Viscosity:**
  - Dynamic:** *Not determined.*
  - Kinematic:** *Not determined.*
- **Solvent content:**
  - VOC content:** *0.00 %*  
*0.0 g/l / 0.00 lb/gl*
- **Solids content:** *22.6 %*
- **Other information** *No further relevant information available.*

## \*10 Stability and reactivity

- **Reactivity** *No further relevant information available.*
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** *No decomposition if used according to specifications.*
- **Possibility of hazardous reactions** *No dangerous reactions known.*
- **Conditions to avoid** *No further relevant information available.*
- **Incompatible materials:** *No further relevant information available.*
- **Hazardous decomposition products:**
  - Nitrogen oxides*
  - Hydrocarbons*
  - Carbon monoxide and carbon dioxide*

## \*11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
  - **on the skin:** *No irritant effect.*
  - **on the eye:** *Irritating effect.*
- **Sensitization:** *No sensitizing effects known.*
- **Additional toxicological information:**
  - The product shows the following dangers according to internally approved calculation methods for preparations:*
  - Irritant*
- **Carcinogenic categories**
- **IARC (International Agency for Research on Cancer)**
  - None of the ingredients is listed.*
- **NTP (National Toxicology Program)**
  - None of the ingredients is listed.*

CA  
(Contd. on page 7)

**Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics**

(Contd. of page 6)

## \* 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 3 (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## \* 14 Transport information

- **UN-Number**
- **DOT, TDG, IMDG, IATA** UN1950
- **UN proper shipping name**
- **DOT** Aerosols, flammable
- **TDG** 1950 Aerosols
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable

- **Transport hazard class(es)**

- **DOT**



- **Class** 2.1

(Contd. on page 8)

CA

**Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics**

(Contd. of page 7)

- **Label** 2.1
- **TDG (Transport dangerous goods):**



- **Class** 2 5F Gases
- **Label** 2.1
- **IMDG, IATA**



- **Class** 2.1
- **Label** 2.1

- **Packing group**
- **DOT, TDG, IMDG, IATA** Void

- **Environmental hazards:**
- **Marine pollutant:** No

- **Special precautions for user** Warning: Gases
- **EMS Number:** F-D,S-U
- **Stowage Code** SW1 Protected from sources of heat.  
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

- **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

- **Transport/Additional information:**

- **DOT**
- **Quantity limitations** On passenger aircraft/rail: 75 kg  
On cargo aircraft only: 150 kg

- **TDG**
- **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity

- **IMDG**
- **Limited quantities (LQ)** 1L

(Contd. on page 9)

CA



**Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics**

(Contd. of page 8)

- **Excepted quantities (EQ)** Code: E0  
Not permitted as Excepted Quantity
- **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

## \*15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**
- **Section 355 (extremely hazardous substances):**  
None of the ingredient is listed.
- **Section 313 (Specific toxic chemical listings):**  
None of the ingredients is listed.
- **TSCA (Toxic Substances Control Act):**  
None of the ingredients is listed.
- **Canadian substance listings:**
- **Canadian Domestic Substances List (DSL)**  
None of the ingredients is listed.
- **Canadian Ingredient Disclosure list (limit 0.1%)**  
None of the ingredients is listed.
- **Canadian Ingredient Disclosure list (limit 1%)**  
None of the ingredients is listed.
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS04



GHS07



GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labeling:**  
Quartz (SiO<sub>2</sub>)  
acetone  
toluene  
titanium dioxide
- **Hazard statements**  
H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H319 Causes serious eye irritation.  
H371 May cause damage to organs.  
H336 May cause drowsiness or dizziness.
- **Precautionary statements**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.

(Contd. on page 10)

CA

**Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics**

(Contd. of page 9)

- P251 Do not pierce or burn, even after use.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P311 IF exposed or concerned: Call a poison center/doctor.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P405 Store locked up.
- P410+P403 Protect from sunlight. Store in a well-ventilated place.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## \*16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** 1-480-451-4451 Lloyd Fields

· **Date of preparation / last revision** 04/09/2018 / 18

· **Abbreviations and acronyms:**

ICAO: International Civil Aviation Organisation

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

· **\* Data compared to the previous version altered.**