
Printing date 04/09/2018

# 1 Identification

- · Product identifier
- · Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics
- · Article number: 3305, 3306, 3307
- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Manufactured for: IAMG International Autobody Marketing Group, 1505 North Hayden Road, Ste.111, Scottsdale, AZ 85257 Information phone: 480.451.4451

- · Information department: 1-87-REFINISH
- · Emergency telephone number: CHEMTREC 1-800-424-9300



Reviewed on 11/02/2015

Printing date 04/09/2018

Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

· Hazard pictograms



· Signal word Danger

#### · Hazard-determining components of labeling:

Quartz (SiO2) acetone toluene titanium dioxide

#### · Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H371 May cause damage to organs.

H336 May cause drowsiness or dizziness.

#### utio

Precautionary statements		
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.	
P211	Do not spray on an open flame or other ignition source.	
P251	Pressurized container: Do not pierce or burn, even after use.	
P260	Do not breathe dust/fume/gas/mist/vapors/spray.	
P264	Wash thoroughly after handling.	
P270	Do not eat, drink or smoke when using this product.	
P280	Wear eye protection / face protection.	
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P308+P311	IF exposed or concerned: Call a poison center/doctor.	
P337+P313	If eye irritation persists: Get medical advice/attention.	
P405	Store locked up.	
P410+P403	Protect from sunlight. Store in a well-ventilated place.	
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 $^{\circ}C/122$ F.	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.	

· Classification system:

NFPA ratings (scale 0 - 4)



Health = 2Fire = 4Reactivity = 3

· HMIS-ratings (scale 0 - 4)



(Contd. on page 3) USA

Page 2/11

Printing date 04/09/2018

Page 3/11

Reviewed on 11/02/2015

Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

(Contd. of page 2)

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

# 3 Composition/information on ingredients

Chemical characterization: Mixtures
 Description:
 Mixtures end the following common

Mixture: consisting of the following components. Weight percentages

· Dangerous components: Void

# 4 First-aid measures

- · Description of first aid measures
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed
   No further relevant information available.

# 5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- **Protective equipment:** Wear self-contained respiratory protective device. Mouth respiratory protective device.

# 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
- Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. • **Reference to other sections**
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

(Contd. on page 4) USA

Printing date 04/09/2018

# Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

(Contd. of page 3)

Page 4/11

See Section 13 for disposal information.

- Protective Action Criteria for Chemicals
- · PAC-1:

None of the ingredients is listed.

· PAC-2:

None of the ingredients is listed.

· PAC-3:

None of the ingredients is listed.

# 7 Handling and storage

- · Handling:
- Precautions for safe handling No special measures required. Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires: Do not spray on a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Keep respiratory protective device available. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric

lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- **Requirements to be met by storerooms and receptacles:** Observe official regulations on storing packagings with pressurized containers.
- Information about storage in one common storage facility: Store away from oxidizing agents.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

• Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
- Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.
- · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5) USA

#### Page 5/11

(Contd. of page 4)

# Safety Data Sheet acc. to OSHA HCS

Printing date 04/09/2018

Reviewed on 11/02/2015

### Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

· Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. *Material of gloves* 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:** Safety glasses



Tightly sealed goggles

# 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- General Information
- · Appearance:
- Form: Color:
- · Odor:
- Odor threshold:
- · pH-value:
- Change in condition Melting point/Melting range: Boiling point/Boiling range:
- · Flash point:
- · Flammability (solid, gaseous):
- · Ignition temperature:
- · Decomposition temperature:
- · Auto igniting:

According to product specification Characteristic Not determined. Not determined. 55 °C -103 °C Not applicable. 405 °C Not determined.

Aerosol

Product is not selfigniting.

(Contd. on page 6) USA Printing date 04/09/2018

Reviewed on 11/02/2015

### Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

	(Contd. of page 5)
· Danger of explosion:	In use, may form flammable/explosive vapour-air mixture. Avoid high heat
· Explosion limits: Lower: Upper:	1.1 Vol % 13 Vol %
• Vapor pressure at 20 °C:	233 hPa
Density at 20 °C: Relative density Vapor density Evaporation rate	0.8163 g/cm <sup>3</sup> Not determined. Not determined. Not applicable.
<ul> <li>Solubility in / Miscibility with Water:</li> </ul>	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
<ul> <li>Solvent content: VOC content:</li> </ul>	0.00 % 0.0 g/l / 0.00 lb/gl
Solids content: • Other information	22.6 % No further relevant information available.

# 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products: Nitrogen oxides
   Hydrocarbons
   Carbon monoxide and carbon dioxide

# 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 7) USA

Printing date 04/09/2018

#### Reviewed on 11/02/2015

### Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer) None of the ingredients is listed.
- **NTP (National Toxicology Program)** None of the ingredients is listed.
- **OSHA-Ca (Occupational Safety & Health Administration)** None of the ingredients is listed.

# 12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

# 14 Transport information

- · UN-Number
- · DOT, ADR, IMDG, IATA
- · UN proper shipping name
- DOT
- · ADR
- ·IMDG
- ·IATA

UN1950

Aerosols, flammable 1950 Aerosols AEROSOLS AEROSOLS, flammable

> (Contd. on page 8) USA

(Contd. of page 6)

Page 7/11

· Transport hazard class(es)

Printing date 04/09/2018

Page 8/11

(Contd. of page 7)

#### Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

· DOT 2.1 · Class 2.1 · Label · ADR · Class 2 5F Gases · Label 2.1 · IMDG, IATA · Class 2.1 · Label 2.1 · Packing group · DOT, ADR, IMDG, IATA Void · Environmental hazards: · Marine pollutant: No Warning: Gases · Special precautions for user EMS Number: F-D.S-Ŭ SW1 Protected from sources of heat. Stowage Code SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation Code Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. · Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code

Not applicable.

(Contd. on page 9) USA

Printing date 04/09/2018

Reviewed on 11/02/2015

### Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

(Contd. of page 8)

· Transport/Additional information:	
· DOT · Quantity limitations	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
<ul> <li>ADR</li> <li>Excepted quantities (EQ)</li> </ul>	<i>Code: E0</i> <i>Not permitted as Excepted Quantity</i>
<ul> <li>IMDG</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>	1L Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

# 15 Regulatory information

- $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara
- Section 355 (extremely hazardous substances): None of the ingredient is listed.
- Section 313 (Specific toxic chemical listings): None of the ingredients is listed.
- **TSCA (Toxic Substances Control Act):** None of the ingredients is listed.
- · Proposition 65
- Chemicals known to cause cancer: None of the ingredients is listed.
- Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed.
- Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed.
- Chemicals known to cause developmental toxicity: None of the ingredients is listed.
- · Cancerogenity categories
- EPA (Environmental Protection Agency) None of the ingredients is listed.
- TLV (Threshold Limit Value established by ACGIH) None of the ingredients is listed.
- NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients is listed.
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 10) USA

Printing date 04/09/2018

#### Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

· Hazard pictograms



· Signal word Danger

#### · Hazard-determining components of labeling:

Quartz (SiO2) acetone toluene titanium dioxide

### · Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H371 May cause damage to organs.

H336 May cause drowsiness or dizziness.

Precautionary sta	atements
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear eye protection / face protection.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P308+P311	IF exposed or concerned: Call a poison center/doctor.
P337+P313	If eye irritation persists: Get medical advice/attention.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
<b>A</b> le <b>e e e f f e f f e f f f f f f f f f f</b>	

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: 1-480-451-4451 Lloyd Fields
- · Date of preparation / last revision 04/09/2018 / 18
- Abbreviations and acronyms:
- ICAO: International Civil Aviation Organisation

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 11) USA

Page 10/11

Printing date 04/09/2018

#### Reviewed on 11/02/2015

#### Trade name: 3305 Gray, 3306 Black, 3307 White MP Flexible Primers for Metal and Plastics

(Contd. of page 10)

DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Aerosol 1: Aerosols – Category 1 Press. Gas: Gases under pressure - Compressed gas Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A STOT SE 2: Specific target organ toxicity (single exposure) – Category 2 • \* Data compared to the previous version altered.

USA