

Safety Data Sheet

Printing date 02/15/2019

Revised On 02/15/2019

1 Identification of the substance and manufacturer

Trade name: 3500 GLOSS BLACK
Product code: PK00980003
Recommended use: Paint and coating applications.
Uses advised against: Any that differs from the recommended use.
Manufacturer/Supplier: ABI/Autobody Brands International,
a division of IAMG/International Autobody Marketing Group
1505 N. Hayden Road, Suite 111
Scottsdale, AZ 85257
1-87-REFINISH
www.advantagerefinish.com
Emergency telephone number: ChemTrec: 800-424-9300

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.
Press. Gas H280 Contains gas under pressure; may explode if heated.
Eye Irrit. 2A H319 Causes serious eye irritation.
Repr. 1B H360 May damage fertility or the unborn child.
STOT SE 3 H336 May cause drowsiness or dizziness.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

Signal word

Hazard statements

Danger

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes serious eye irritation.
May damage fertility or the unborn child.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.
Obtain special instructions before use.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash hands thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Call a poison center/doctor if you feel unwell.
If eye irritation persists: Get medical advice/attention.
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Dispose of contents/container in accordance with local/regional/national/international regulations.

Precautionary statements

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description:

This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	32.27%
74-98-6	propane	18.91%
106-97-8	n-butane	11.11%
64742-89-8	VM&P Naphtha	6.962%
64742-47-8	Mineral Spirits	5.89%
108-88-3	Toluene	4.84%
67-63-0	Isopropyl Alcohol	2.92%
1330-20-7	xylene (mix)	2.14%

4 First-aid measures

After inhalation:

Supply fresh air; consult doctor in case of complaints.

After skin contact:

Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects:

Dizziness

Indication of any immediate medical attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

(Contd. on page 2)

Safety Data Sheet

Printing date 02/15/2019

Revised On 02/15/2019

Trade name: 3500 GLOSS BLACK

Special hazards:

Can form explosive gas-air mixtures.

(Contd. of page 1)

Protective equipment for firefighters:

A respiratory protective device may be necessary.

6 Accidental release measures**Personal precautions, protective equipment and emergency procedures:**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

7 Handling and storage**Precautions for safe handling**

Use only in well ventilated areas.

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:****67-64-1 Acetone**PEL (USA) Long-term value: 2400 mg/m³, 1000 ppmREL (USA) Long-term value: 590 mg/m³, 250 ppmTLV (USA) Short-term value: 1187 mg/m³, 500 ppmLong-term value: 594 mg/m³, 250 ppm

BEI

74-98-6 propanePEL (USA) Long-term value: 1800 mg/m³, 1000 ppmREL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) refer to Appendix F in TLVs&BEIs book; D, EX

106-97-8 n-butaneREL (USA) Long-term value: 1900 mg/m³, 800 ppmTLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

(EX)

108-88-3 ToluenePEL (USA) Long-term value: 200 ppm
Ceiling limit value: 300; 500* ppm
*10-min peak per 8-hr shiftREL (USA) Short-term value: 560 mg/m³, 150 ppmLong-term value: 375 mg/m³, 100 ppmTLV (USA) Long-term value: 75 mg/m³, 20 ppm

BEI

67-63-0 Isopropyl AlcoholPEL (USA) Long-term value: 980 mg/m³, 400 ppmREL (USA) Short-term value: 1225 mg/m³, 500 ppmLong-term value: 980 mg/m³, 400 ppmTLV (USA) Short-term value: 984 mg/m³, 400 ppmLong-term value: 492 mg/m³, 200 ppm

BEI

1330-20-7 xylene (mix)PEL (USA) Long-term value: 435 mg/m³, 100 ppmREL (USA) Short-term value: 655 mg/m³, 150 ppmLong-term value: 435 mg/m³, 100 ppmTLV (USA) Short-term value: 651 mg/m³, 150 ppmLong-term value: 434 mg/m³, 100 ppm

BEI

Ingredients with biological limit values:**67-64-1 Acetone**

BEI (USA) 50 mg/L

Medium: urine

Time: end of shift

Parameter: Acetone (nonspecific)

67-63-0 Isopropyl Alcohol

BEI (USA) 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

1330-20-7 xylene (mix)

BEI (USA) 1.5 g/g creatinine

Medium: urine

Time: end of shift

Parameter: Methylhippuric acids

Hygienic protection:

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Store protective clothing separately.

(Contd. on page 3)

Safety Data Sheet

Printing date 02/15/2019

Revised On 02/15/2019

Trade name: 3500 GLOSS BLACK

(Contd. of page 2)

Breathing equipment:	Avoid contact with the eyes and skin. Do not eat or drink while working. A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.
Hand protection:	Nitrile gloves. The glove material must be impermeable and resistant to the substance.
Eye protection:	Tightly sealed goggles

9 Physical and chemical properties

Appearance:	Aerosol.
Odor:	Aromatic
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-44 °C (-47.2 °F)
Flash point:	-19 °C (-2.2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.5 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapor density	Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octanol/water:	Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.
VOC content (less exempt solvents):	48.6 %

10 Stability and reactivity

Reactivity:	Stable at normal temperatures.
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability:	Not fully evaluated.
Possibility of hazardous reactions:	No dangerous reactions known.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

67-63-0 Isopropyl Alcohol

Oral	LD50	4,570 mg/kg (rat)
Dermal	LD50	13,400 mg/kg (rab)
Inhalative	LC50/4 h	30 mg/l (rat)

1330-20-7 xylene (mix)

Oral	LD50	8,700 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rbt)
Inhalative	LC50/4 h	6,350 mg/l (rat)

Information on toxicological effects:	No data available.
Skin effects:	No irritant effect.
Eye effects:	Irritating effect.
Sensitization:	No sensitizing effects known.

12 Ecological information

Aquatic toxicity:	Hazardous for water, do not empty into drains.
Persistence and degradability:	The product is degradable after prolonged exposure to natural weathering processes.
Other information:	This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.
Bioaccumulative potential:	No further relevant information available.
Mobility in soil:	No further relevant information available.
Other adverse effects:	No further relevant information available.

(Contd. on page 4)

Safety Data Sheet

Printing date 02/15/2019

Revised On 02/15/2019

Trade name: 3500 GLOSS BLACK

(Contd. of page 3)

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number	UN1950
DOT	N/A
DOT	Consumer Commodity ORM-D
ADR	Aerosols, flammable
Transport hazard class(es):	1950 Aerosols
Class	2.1
Marine pollutant:	No
Special precautions for user:	Warning: Gases
EMS Number:	F-D,S-U
Packaging Group:	--
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

15 Regulatory information**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3	Toluene
67-63-0	Isopropyl Alcohol
1330-20-7	xylene (mix)

Toxic Substances Control Act (TSCA):

All hazardous ingredients for this product are found on the inventory list of substances.

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

1333-86-4	Carbon black
100-41-4	ethyl benzene

California Proposition 65 chemicals known to cause birth defects or reproductive harm:

108-88-3	Toluene
----------	---------

CANADIAN ENVIRONMENTAL PROTECTION ACT:

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

EPA:

67-64-1	Acetone	I
1330-20-7	xylene (mix)	I

16 Other information

Contact: Regulatory Affairs