



SDS/TDS/Photos

PREMIUM ADHESION PROMOTER

An all-purpose clear primer that improves adhesion of enamel and lacquer topcoats to nearly any surface, including most plastics and chrome. It is fast drying and provides superior adhesion on all flexible and rigid plastic parts. Features a sprayhead for spray gun-like application. Topcoat after 10 minutes, and before 30 minutes for maximum adhesion.

SUGGESTED USES:

- Glass Ð
- Chrome (+)
- Ceramic/Tile
- Vinvl (Ð
- **Bumpers** (\pm)
- **Fiberglass** Ŧ
- Aluminum Ð
- Polypropylene (\pm)
- **Polycarbonate** ŧ
- **Molded Trim Pieces** Ŧ

CAUTION: MAY ATTACK SOME TYPE OF SOFT PLASTICS.

FOR MANY INDUSTRIES



You Tube

Application Video Link

Call 1-87REFINISH (1-877-334-6474) to find your local 5 STAR ADVANTAGE Refinish Products® Supplier, or visit our websites: www.5starxtreme.com / www.advantagerefinish.com SDS/TDS/Photos available ©2020 Part 5STA#3530 (supersedes 5STX#5961)

ADHESION PROMOTER

PREMIUM

USES: ALUMINUM, FIBERGLASS, VINYL, MOLDED TRIM, USES: ALUMINOW, HERKGLASS, VINTL, MOLDED IAIM, PLASTIC, BUMPERS, GLASS, CHROME, METAL AND TILE. EASY TO USE FAN SPRAY TIP, FAST DRY - TOPCOAT AFTER 10 MINS, BEFORE 30 MINS FOR MAX ADHESION OF SOLVENT-BASED ENAMEL & LACQUER TOPCOATS.

PROMQTEUR **D'ADHÉSION** PREMIUM

UTILISATIONS: ALUMINIUM, FIBRE DE VERRE, VINYLE GARNITURE MOULÉE, PLASTIQUE, PARE-CHOCS, VERRE, CHROME, MÉTAL ET TUILE. ASTUCE DE PULVÉRISATION FACILI À UTILISER. FAST DRY - TOPCOAT APRÈS 10 MINS, AVANT 30 MINS POUR UNE ADHÉRENCE MAXIMALE DE FINITIONS À BASE D'ÉMAIL ET DE LAQUE À BASE DE SOLVANTS.

> 3530 5starxtreme.com | advantagerefinish.com

Net wt. 15 oz / 425 g Poids Net 425g / Peso Net 425g FOR PROFESSIONAL USE ONLY

X

a < 😽 m DANGER EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPORS MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE. VAPOR MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSOR VAPOR HARMFUL. See other cautions on back panel. DANGER Liquide et vapeurs extrêmement inflammables. Les vapeurs peuvent causer un incendie. Contenus ous pression. Vapeur nocive. Voir PELIGRO Liquido y vapores extremadamente inflamables. Los vapores ueden causar un incendie. Contenido bajo presión. Vapor nociv Ver dras precauciones al dorso. Ver otras precauciones al dorso.



#3530 - Premium Adhesion Promoter Aerosol (15 fl. oz) (supersedes 5STX#5961)