







SDS/TDS/Photos



BLACK

OM

INTURE

**NTE** 

ITILATEUR

HIMIQUES

O MINS

25 g let 425g

ISE ONLY

is on back panel.

meau arrière

IQUID AND VAPOR. TS UNDER PRESSURE.

flammables. Les vapeurs

ssion. Vapeur nocive. Voi

nflamables. Los vapores o bajo presión. Vapor noc

R DE

Trim paint is formulated using an acrylic resin that resists fading from ultraviolet light and degradation from chemicals. Spray like a professional without the equipment, prep time, cleanup, or waste. Several light coats produce a better finish than one heavy coat. A heavy coat applied over an enamel may cause lifting. Bare surfaces or rusted metal surfaces should first be primed with the 5 STAR ADVANTAGE #3525 Sandable

## **SUGGESTED USES:**

Primer.

- **Body Panels & Metal Structures**
- **Engine & Aviation Parts**
- **Heavy Machinery**

## **SPECIAL FEATURES:**

- **Large Fan Spray Head**
- Dry to the touch in 20 mins.
- **Resists fading from UV light & chemicals**



#3532 - Trim Paint Aerosol (15 fl. oz) Gloss Black

#3533 - Trim Paint Aerosol (15 fl. oz) Flat Black

#3534 - Trim Paint Aerosol (15 fl. oz) Semi-Gloss Black

Call 1-87REFINISH (1-877-334-6474) to find your local 5 STAR ADVANTAGE Refinish Products® Supplier, or visit our websites: www.5starxtreme.com / www.advantagerefinish.com SDS/TDS/Photos available ©2020 Part 5STA#3532/3533/3534