

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2020

Revised On 04/20/2020

## 1 Identification

**Trade name:** 3534 TRIM PAINT SEMI GLOSS BLACK

**Product code:** PK00201679

**Recommended use:** Paint and coatings application.

**Uses advised against:** Any that differs from the recommended use.

**Manufacturer/Supplier:** ABI/Autobody Brands International,  
a division of of IAMG/International Autobody Marketing Group  
1505 N. Hayden Road, Suite 111  
Scottsdale, AZ 85257  
1-87-REFINISH  
www.5starxtreme.com / www.advantagerefinish.com  
ChemTrec: 800-424-9300

**Emergency telephone number:**

## 2 Hazard(s) identification

### Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Repr. 1B H360 May damage fertility or the unborn child.

STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

### GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

### Signal word

Danger

### Hazard-determining components of labeling:

Toluene  
Acetone  
butyl acetate

### Hazard statements

Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.  
Causes skin irritation.  
Causes serious eye irritation.  
May damage fertility or the unborn child.  
May cause drowsiness or dizziness.

### Precautionary statements

May cause damage to organs through prolonged or repeated exposure.  
Obtain special instructions before use.  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Do not spray on an open flame or other ignition source.  
Pressurized container: Do not pierce or burn, even after use.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Wash hands thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/protective clothing/eye protection/face protection.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Call a poison center/doctor if you feel unwell.  
Specific treatment (see on this label).  
Take off contaminated clothing and wash it before reuse.  
If eye irritation persists: Get medical advice/attention.  
Store in a well-ventilated place.  
Store locked up.  
Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
Dispose of contents/container in accordance with local/regional/national/international regulations.

### Physical dangers:

### Effects of chronic overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

## 3 Composition/information on ingredients

### Chemical characterization: Mixtures

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

### Dangerous components:

67-64-1	Acetone	25-50%
74-98-6	propane	15-25%
108-88-3	Toluene	10-15%

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2020

Revised On 04/20/2020

Trade name: 3534 TRIM PAINT SEMI GLOSS BLACK

(Contd. of page 1)

106-97-8	n-butane	5-10%
123-86-4	butyl acetate	5-10%
108-65-6	PM acetate	1-5%

## 4 First-aid measures

### Description of first aid measures

After inhalation:	Supply fresh air; consult doctor in case of complaints.
After skin contact:	Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact:	Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
After swallowing:	Rinse mouth with water. Do not induce vomiting.
Information for doctor:	
Most important symptoms and effects:	Dizziness
Indication of any immediate medical attention needed:	No further relevant information available.

## 5 Fire-fighting measures

Extinguishing media	
Extinguishing agents:	CO2, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards:	Can form explosive gas-air mixtures.
Protective equipment for firefighters:	A respiratory protective device may be necessary.
Additional information	Cool endangered receptacles with water spray.

## 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:	Use respiratory protective device against the effects of fumes/dust/aerosol.
Environmental precautions:	Do not allow product to reach sewage systems or ground water.
Methods and material for containment and cleaning up:	Absorb liquid components with liquid-binding material.

## 7 Handling and storage

Precautions for safe handling	Use only in well ventilated areas.
Fire/explosion protection:	Keep respiratory protective device available. Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.
Conditions for safe storage:	
Storage requirements:	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

## 8 Exposure controls/personal protection

### Components with limit values that require monitoring at the workplace:

#### 67-64-1 Acetone

PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV	Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm
	Long-term value: 594 mg/m <sup>3</sup> , 250 ppm
BEI	

#### 74-98-6 propane

PEL	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
TLV	refer to Appendix F in TLVs&BEIs book; D, EX

#### 108-88-3 Toluene

PEL	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
REL	Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm
TLV	Long-term value: 75 mg/m <sup>3</sup> , 20 ppm BEI

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2020

Revised On 04/20/2020

Trade name: 3534 TRIM PAINT SEMI GLOSS BLACK

(Contd. of page 2)

**106-97-8 n-butane**

REL	Long-term value: 1900 mg/m <sup>3</sup> , 800 ppm
TLV	Short-term value: 2370 mg/m <sup>3</sup> , 1000 ppm (EX)

**123-86-4 butyl acetate**

REL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
REL	Short-term value: 950 mg/m <sup>3</sup> , 200 ppm
REL	Long-term value: 710 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm
TLV	Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

**108-65-6 PM acetate**

WEEL	Long-term value: 50 ppm
------	-------------------------

**Ingredients with biological limit values:****67-64-1 Acetone**

BEI	50 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Acetone (nonspecific)

**Exposure controls****Hygienic protection:**

Immediately remove all soiled and contaminated clothing.  
Wash hands after use.  
Store protective clothing separately.  
Do not eat or drink while working.

**Breathing equipment:**

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:**

Nitrile gloves.

**Eye protection:**

The glove material must be impermeable and resistant to the substance.  
Tightly sealed goggles

**9 Physical and chemical properties****General Information:**

<b>Appearance:</b>	Aerosol.
<b>Odor:</b>	Aromatic
<b>Odor threshold:</b>	Not determined.

<b>pH-value:</b>	Not determined.
------------------	-----------------

<b>Melting point/Melting range</b>	Undetermined.
------------------------------------	---------------

<b>Boiling point:</b>	-44.5 °C (-48.1 °F)
-----------------------	---------------------

<b>Flash point:</b>	-19 °C (-2.2 °F)
---------------------	------------------

<b>Decomposition temperature:</b>	Not determined.
-----------------------------------	-----------------

<b>Auto igniting:</b>	Product is not self-igniting.
-----------------------	-------------------------------

<b>Danger of explosion:</b>	Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit. In use, may form flammable/explosive vapour-air mixture.
-----------------------------	---

<b>Lower Explosion Limit:</b>	1.7 Vol %
-------------------------------	-----------

<b>Upper Explosion Limit:</b>	10.9 Vol %
-------------------------------	------------

<b>Vapor pressure:</b>	40 PSI      2750 hPa
------------------------	----------------------

<b>Vapor Pressure:</b>	40 PSI, 2750 hPa
------------------------	------------------

<b>Relative Density:</b>	Between 0.77 and 0.85 (Water equals 1.00)
--------------------------	---

<b>Vapor density</b>	Not determined.
----------------------	-----------------

<b>Evaporation rate</b>	Not applicable.
-------------------------	-----------------

<b>Partition coefficient: n-octonal/water:</b>	Not determined.
--	-----------------

<b>Solubility:</b>	Not determined.
--------------------	-----------------

<b>Viscosity:</b>	Not determined.
-------------------	-----------------

<b>Dynamic:</b>	Not determined.
-----------------	-----------------

<b>Kinematic:</b>	Not determined.
-------------------	-----------------

<b>Water:</b>	0.0 %
---------------	-------

**10 Stability and reactivity**

<b>Conditions to avoid:</b>	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
-----------------------------	--

<b>Possibility of hazardous reactions:</b>	No dangerous reactions known.
--	-------------------------------

<b>Conditions to avoid</b>	No further relevant information available.
----------------------------	--

<b>Incompatible materials:</b>	No further relevant information available.
--------------------------------	--

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2020

Revised On 04/20/2020

Trade name: 3534 TRIM PAINT SEMI GLOSS BLACK

**Hazardous decomposition:** No dangerous decomposition products known.

(Contd. of page 3)

## 11 Toxicological information

### LD/LC50 values that are relevant for classification:

#### 123-86-4 butyl acetate

Oral	LD50	14,000 mg/kg (rat)
Inhalative	LC50/4 h	>21 mg/l (rat)

#### 108-65-6 PM acetate

Oral	LD50	8,500 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)

**Skin effects:** No irritant effect.  
**Eye effects:** Irritating effect.  
**Sensitization:** No sensitizing effects known.

### IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

### NTP (National Toxicology Program)

None of the ingredients is listed.

## 12 Ecological information

**Toxicity**  
**Aquatic toxicity:** Hazardous for water, do not empty into drains.  
**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.  
**Other information:** This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.  
**Bioaccumulative potential:** No further relevant information available.  
**Mobility in soil:** No further relevant information available.  
**Results of PBT and vPvB assessment**  
**PBT:** Not applicable.  
**vPvB:** Not applicable.  
**Other adverse effects:** No further relevant information available.

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

### Waste treatment methods

**Recommendation:** Completely empty cans should be recycled.

## 14 Transport information

<b>UN-Number</b>	UN1950
<b>DOT</b>	N/A
<b>UN proper shipping name:</b>	
<b>DOT</b>	Consumer Commodity ORM-D Aerosols, flammable
<b>Transport hazard class(es):</b>	
<b>Class</b>	2.1
<b>Special precautions for user:</b>	Warning: Gases
<b>EMS Number:</b>	F-D,S-U
<b>Packaging Group:</b>	--

## 15 Regulatory information

**Toxic Substances Control Act (TSCA):** All hazardous ingredients are found on the inventory list of substances.  
**Consumer Product Safety Commission (CPSC):** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

### Hazardous Air Pollutants

108-88-3 Toluene

### California Proposition 65 chemicals known to cause cancer:

1333-86-4 Carbon black

### Prop 65 chemicals known to cause birth defects or reproductive harm:

108-88-3 Toluene

### CANADIAN ENVIRONMENTAL PROTECTION ACT:

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2020

Revised On 04/20/2020

Trade name: 3534 TRIM PAINT SEMI GLOSS BLACK

(Contd. of page 4)

**EPA:**

67-64-1 Acetone

I

**GHS label elements****Precautionary statements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Chemical safety assessment:**

A Chemical Safety Assessment has not been carried out.

**16 Other information**

This product was manufactured in the U.S.A.

The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Contact:**

Regulatory Affairs

**Date of preparation / last revision**

04/21/2020 / -

**Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

EPA: Environmental Protection Agency

IARC: International Agency for the Research of Cancer

NIOSH: National Institute for Occupational Safety and Health

TSCA: Toxic Substances Control Act

CPSC: Consumer Product Safety Commission

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Aerosol 1: Aerosols – Category 1

Press. Gas: Gases under pressure – Liquefied gas

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Repr. 1B: Reproductive toxicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2