



SDS/TDS/Photos

SETAR ADVANTAGE. AUTOBODY PRODUCTS LIGHT GRAY PRIMER SPRAY

USE ON MOST TYPES OF BARE METAL AND

WOOD SURFACES. PROVIDES
EXCELLENT ADHESION FOR FINISH COAT.
CAN BE TOP-COATED WITHIN 20 MINS.

SPRAY D'APPRÊT

GRIS CLAIR

UTILISATION SUR LA PLUPARTE DES TYPES DE MÉTAUX
NUS ET SURFACES EN BOIS. FOURNIT
EXCELLENTE ADHÉRENCE POUR LA COUCHE DE

EINITION. PEUT ÊTRE REVÊTU EN 20 MINS.

Net wt. 12 oz / 340 g Poids Net 340 g / Peso Net 340 g

FOR PROFESSIONAL USE ONLY

DÂNGER EXTREMELY FLAMMABLE LIQUID AND VAPOR.
VAPORS MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE.
VAPOR HARMFUL. See other cautions on back panel.
DANGER Liquide et vapeurs extrêmement inflammables. Les vapeurs
peuvent causer un incendie. Contenus ous pression. Vapeur nocive. Voir

PELIGRO Liquido y vapores extremadamente inflamables. Los vapores ueden causar un incendio instantaneo. Contenido bajo presión. Vapor nociv

Ver otras precauciones al dorso

5 starxtreme com adva

LIGHT GRAY PRIMER SPRAY

A fast drying spray primer that provides maximum rust protection and adhesion for a finishing top coat. Can be used with lacquer, enamel, and acrylic paints. Provides excellent resistance to heat and corrosion while being sandable. VOC compliant. For best results, sand lightly with fine sandpaper or steel wool prior to applying finish coat. Can be top-coated in 20 minutes.

SUGGESTED USES:

- Wood
- Bare Metal
- Machinery
- Engine Blocks
- Vehicle Parts

DRY TIME*:

- ◆ To Touch 5 minutes
- To Topcoat 20 minutes
 *at 72°F, 50% Humidity
 1.5mil thickness
- Curing/Recoat time is extended with multiple coats and excessively thick coats.

3711

#3711 - Light Gray Primer Spray Aerosol (12 fl. oz) Call 1-87REFINISH (1-877-334-6474) to find your local 5 STAR ADVANTAGE Refinish Products® Supplier, or visit our websites: www.5starxtreme.com / www.advantagerefinish.com SDS/TDS/Photos available ©2020 Part 5STA#3711