

POLYESTER PREMIUM FINISHING PUTTY

5 STAR #5068 Polyester Premium Finishing Putty - 12oz. pouch
Ideal for use on scratches, pinholes, minor imperfections and last minute fixes. Formulated with a new additive for enhanced adhesion, #5068 flows and levels to provide a fast curing, ultra smooth surface.

PRODUCT FEATURES/BENEFITS:

Enhanced Adhesion Quick Cure and Sand
Ultra Smooth Finish Seamless Featheredge
Micro-Perfecting Surface Technology self-level to a high-density, pinhole free surface that powders to a perfect finish.

DIRECTIONS:

NOTE: Wear protective glasses and gloves and use a respiratory covering to protect from dust.

PREPARATION: Area to be filled must be sanded and free of dirt, grease, oil, wax and rust. For best results, use at temperatures above 68°F.

MIXING: Knead the supplied 5 STAR cream hardener tube prior to using. Combine the putty and hardener 2% by weight, or 1-1/2" ribbon of hardener to a 4" puddle of putty. Mix quickly and to an even color consistency. Mix only enough material to be used in 3 minutes. Do not return unused mixture to the pouch.

APPLICATION: With a spreader, apply mixed material to repair area. Fill should not exceed 1/8 inch in depth. Allow to cure approximately 15 minutes.

FINISH: After curing, sand with 180 grit paper to start. Finish sand with 220 to 400 grit paper prior to priming or sealing. Refer to paint manufacturer's instructions for topcoat application.

Polyester Premium Finishing Putty Available:

#5068 - NEW! 12oz. pouch

#5066 - 16oz. tube

#5067 - 30oz. pumptainer

**CONVENIENT
SIZE!**

5 STAR™
AUTOBODY PRODUCTS



#5068



INSTANT MSDS

Scan this QR Code with your SMART PHONE for instant MSDS and TDS information.

Call 1-87REFINISH (1-877-334-6474) to find your local 5 STAR Autobody Products supplier.
Or visit our website: www.autobodybrands.com - MSDS/TDS/High Resolution photos available
©2014 Part #5068