

**5 STAR XTREME AUTOBODY PRODUCTS**  
**TECHNICAL DATA INFORMATION**  
**DATED: MARCH 2012**

**PRODUCT NUMBER DESCRIPTION**

#5125 – GLAMOUR HS KLEARKOTE 4.2 VOC

**PRODUCT DESCRIPTION:**

#5125 is a high quality, high solids acrylic urethane clearcoat for spot, multi-panel or overall repairs. Formulated to be applied over basecoat systems. Excellent for custom painters.  
4.2 VOC, Mix Ratio of 2:1.

**PRODUCTS:**

<b>PART #</b>	<b>PRODUCT DESCRIPTION</b>	<b>SIZE</b>
#5125-01	Glamour HS Klearkote	Gallon
#5125-04	Glamour HS Klearkote	Quart
#5152-04	Glamour Activator Spot - Fast	Quart
#5150-04	Glamour Activator Panel - Medium	Quart
#5150-08	Glamour Activator Panel - Medium	Pint
#5160-04	Glamour Activator Multi-Panel/ Overall - Slow	Quart

**MIXING RATIO (2:1):**

2 parts of #5125 Glamour HS Klearkote to 1 part #5152/#5150/#5160 Glamour HS Activator.

**APPLICATION:**

- 1.) Adjust air pressure to 45-50 psi (Siphon); 35-40 (Gravity); 8-10 (HVLP).
- 2.) Apply 1 medium coat followed by 1 full wet coat.
- 3.) Allow 10-15 minutes flash time between coats.
- 4.) 40 minutes @ 140F for traditional baking situations.
- 5.) Allow to dry overnight before exposing to the weather.

**GUN SETUPS:**

**CONVENTIONAL**

Gravity Feed: 35 - 40 psi  
Siphon Feed: 45 - 50 psi  
HVLP @ Cap: 8 - 10 psi

**FLASH/DRY TIMES:**

Dust Free: 15-20 Minutes  
Tack Free: 60 Minutes  
Wet Sand: 16-24 Hours  
Buffable: 16-24 Hours  
Delivery: Overnight

**CLEAN UP:**

Clean equipment immediately using 5 STAR XTREME #5700 Premium Lacquer Thinner or Urethane Reducer.

**TECH DATA:**

**Color:** Water White

**Mixing Ratio:** 2:1

**Catalyst:** #5150 Panel, #5152 Spot, #5160 Multi-Panel/Overall

**Viscosity (Sprayable):** 18-20 seconds #2 Zahn

**Suggested Fluid Tip Size**

**Siphon** (1.3mm - 1.5mm) **Gravity** (1.3mm - 1.5mm) **HVLP** (1.3mm - 1.5mm)

**Volume Solids (Sprayable):** 50%

**Film Build :** 1.5 - 2.0 mils wet

**Coverage:** 810 sq. ft. per gallon at 1 mil

**VOC:** 4.2 lbs/gallon (RTS)

**Pot Life:** 5 hours

**FIRST AID:**

In case of eye contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention. For skin: Wash thoroughly with water. If difficulty in breathing is experienced, get medical attention immediately. If swallowed, do not induce vomiting, get medical attention immediately. See Material Safety Data Sheet.

**SAFETY INFORMATION - FOR INDUSTRY USE ONLY**

Danger: Vapor and spray mist harmful. Overspray may cause lung damage. May cause allergic skin and respiratory reaction, effects may be permanent. Flammable liquid and vapor. Harmful if inhaled. May affect the brain or nervous system causing dizziness, headache, or nausea. May cause eye, skin, nose, and throat irritation. Contents: See product label for contents and CAS #'s. The contents of this package must be blended with other components before the product can be used. Any mixture of components will have hazards of all components. Before opening the packages, read all warning labels. Follow all precautions. The material is designed for application only by professional trained personnel using proper equipment under controlled conditions, and is not intended for sale to the general public.

**KEEP OUT OF REACH OF CHILDREN.**

ABI/Autobody Brands International a division of IAMG/International Autobody Marketing Group - Scottsdale, AZ - [www.autobodybrands.com](http://www.autobodybrands.com)