



# PRIMED *for* SUCCESS

**NEW!**

## 5 STAR XTREME HIGH BUILD EPOXY PRIMER/SEALER (GRAY)

#5433 has been formulated for excellent adhesion and corrosion resistance when used on various types of substrates including properly prepared steel and aluminum. When mixed properly, #5433 is compliant with all known Canadian and US rules including SCAQMD Rule 1151.



**2.1  
VOC**

### FEATURES

**EXCELLENT  
ADHESION**

**EXCELLENT  
CORROSION  
RESISTANCE**

### MIX RATIO


HIGH BUILD EPOXY PRIMER/SEALER

1:1:15-25% MIX RATIO

#5433 Primer: #5434 Catalyst

(SANDING FILLER) Reduce 15-20% with a LOW VOC Reducer for compliancy.

At 25% for Sealer option.



Scan this **QR Code** with your **SMART PHONE**  
for instant **MSDS** and **TDS** information.  
#5433-01



#5433-01 High Build Epoxy Primer/Sealer (2.1 VOC), Gallon

#5433-04 High Build Epoxy Primer/Sealer (2.1 VOC), Quart

#5434-01 High Build Epoxy Primer/Sealer Catalyst (2.1 VOC), Gallon

#5434-04 High Build Epoxy Primer/Sealer Catalyst (2.1 VOC), Quart



Call 1-87REFINISH (1-877-334-6474) to find your local 5 STAR XTREME Autobody Products supplier, or visit our website: [www.5starxtreme.com](http://www.5starxtreme.com) - MSDS/TDS/High Resolution photos available ©2014 Part #5433/#5434