

Safety Data Sheet

acc. to OSHA HCS

Printing date

Reviewed on

1 Identification

- **Product identifier**

- **Trade name:** 2K RAPID FILL PRIMER

- **Article number:** 5480-01

- **Details of the supplier of the safety data sheet**

MANUFACTURED FOR : 5 STAR XTREME Autobody Products
A division of IAMG/International Autobody Marketing Group

ADDRESS : 1505 North Hayden Road, Ste. 111 Scottsdale, AZ 85257

Web Site: www.5starxtreme.com

EMERGENCY PHONE : (800)424-9300 (24 hrs.)

2 Hazard(s) identification

- **Classification of the substance or mixture**

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Irritant

Irritating to skin.

Flammable.

- **Information concerning particular hazards for human and environment:**

The product has to be labeled due to the calculation procedure of international guidelines.

- **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- **Label elements**

- **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with directives on hazardous materials.

- **Code letter and hazard designation of product:**



Irritant

- **Risk phrases:**

Flammable.

Irritating to skin.

- **Safety phrases:**

Keep out of the reach of children.

Keep away from sources of ignition - No smoking.

If swallowed, seek medical advice immediately and show this container or label.

Dispose of this material and its container to hazardous or special waste collection point.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

(Contd. on page 2)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date

Reviewed on

Trade name: 2K RAPID FILL PRIMER

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4)

HEALTH	1	Health = 1
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	10-25%
1330-20-7	xylene	2.5-10%
79-20-9	methyl acetate	2.5-10%
100-41-4	ethylbenzene	½ 2.5%
123-86-4	n-butyl acetate	½ 2.5%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date

Reviewed on

Trade name: 2K RAPID FILL PRIMER

(Contd. of page 2)

- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 3
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

· Components with limit values that require monitoring at the workplace:

1330-20-7 xylene

PEL ()	Long-term value: 435 mg/m ³ , 100 ppm
REL ()	Short-term value: 655 mg/m ³ , 150 ppm
	Long-term value: 435 mg/m ³ , 100 ppm
TLV ()	Short-term value: 651 mg/m ³ , 150 ppm
	Long-term value: 434 mg/m ³ , 100 ppm
	BEI

79-20-9 methyl acetate

PEL ()	Long-term value: 610 mg/m ³ , 200 ppm
REL ()	Short-term value: 760 mg/m ³ , 250 ppm
	Long-term value: 610 mg/m ³ , 200 ppm
TLV ()	Short-term value: 757 mg/m ³ , 250 ppm
	Long-term value: 606 mg/m ³ , 200 ppm

100-41-4 ethylbenzene

PEL ()	Long-term value: 435 mg/m ³ , 100 ppm
--------	--

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date

Reviewed on

Trade name: 2K RAPID FILL PRIMER

(Contd. of page 3)

REL ()	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV ()	Short-term value: 543 mg/m ³ , 125 ppm Long-term value: 87 mg/m ³ , 20 ppm BEI

123-86-4 n-butyl acetate

PEL ()	Long-term value: 710 mg/m ³ , 150 ppm
REL ()	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV ()	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 713 mg/m ³ , 150 ppm

Ingredients with biological limit values:**1330-20-7 xylene**

BEI ()	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
--------	--

100-41-4 ethylbenzene

BEI ()	0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

• **Additional information:** The lists that were valid during the creation were used as basis.

• **Exposure controls**• **Personal protective equipment:**• **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

• **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date

Reviewed on

Trade name: 2K RAPID FILL PRIMER

(Contd. of page 4)

substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

• **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

• **Information on basic physical and chemical properties**

• **General Information**

• **Appearance:**

Form:	Liquid
Color:	Grey
Odor:	Characteristic
Odour threshold:	Not determined.

• **pH-value:** Not determined.

• **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	136 °C (277 °F)

• **Flash point:** 25 °C (77 °F)

• **Flammability (solid, gaseous):** Not applicable.

• **Ignition temperature:** 500 °C (932 °F)

• **Decomposition temperature:** Not determined.

• **Auto igniting:** Product is not selfigniting.

• **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

• **Explosion limits:**

Lower:	1.1 Vol %
Upper:	7.0 Vol %

• **Vapor pressure at 20 °C (68 °F):** 6.7 hPa (5 mm Hg)

• **Density at 20 °C (68 °F):** 1.63 g/cm³ (13.602 lbs/gal)

• **Relative density** Not determined.

• **Vapour density** Not determined.

• **Evaporation rate** Not determined.

• **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

• **Partition coefficient (n-octanol/water):** Not determined.

• **Viscosity:**

Dynamic: Not determined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date

Reviewed on

Trade name: 2K RAPID FILL PRIMER

(Contd. of page 5)

Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	30.8 %
VOC content:	13.4 %
	282.3 g/l / 2.36 lb/gal
· Solids content:	69.1 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

13463-67-7	titanium dioxide	2B
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
7647-01-0	hydrogen chloride	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

USA

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date

Reviewed on

Trade name: 2K RAPID FILL PRIMER

(Contd. of page 6)


12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 2 (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|----------------------|
| · UN-Number | UN1263 |
| · DOT, ADR, IMDG, IATA | |
| · UN proper shipping name | Paint |
| · DOT | 1263 Paint |
| · ADR | PAINT |
| · IMDG, IATA | |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 3 Flammable liquids. |
| · Label | 3 |

(Contd. on page 8)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date

Reviewed on

Trade name: 2K RAPID FILL PRIMER

(Contd. of page 7)

· ADR, IMDG, IATA



· Class 3 Flammable liquids
 · Label 3

· Packing group
 · DOT, ADR, IMDG, IATA III

· Environmental hazards:
 · Marine pollutant: No

· Special precautions for user Warning: Flammable liquids
 · Danger code (Kemler): 30
 · EMS Number: F-E, S-E

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture
 · Sara

· Section 355 (extremely hazardous substances):

7647-01-0	hydrogen chloride
-----------	-------------------

· Section 313 (Specific toxic chemical listings):

1330-20-7	xylene
-----------	--------

100-41-4	ethylbenzene
----------	--------------

7647-01-0	hydrogen chloride
-----------	-------------------

· TSCA (Toxic Substances Control Act):

13463-67-7	titanium dioxide
------------	------------------

98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene
---------	---

1330-20-7	xylene
-----------	--------

79-20-9	methyl acetate
---------	----------------

100-41-4	ethylbenzene
----------	--------------

123-86-4	n-butyl acetate
----------	-----------------

57-55-6	propane-1,2-diol
---------	------------------

64-19-7	acetic acid
---------	-------------

763-69-9	ethyl 3-ethoxypropionate
----------	--------------------------

77-58-7	dibutyltin dilaurate
---------	----------------------

108-65-6	2-methoxy-1-methylethyl acetate
----------	---------------------------------

7647-01-0	hydrogen chloride
-----------	-------------------

78-83-1	butanol
---------	---------

(Contd. on page 9)

USA

Safety Data Sheet

acc. to OSHA HCS

Printing date

Reviewed on

Trade name: 2K RAPID FILL PRIMER

(Contd. of page 8)

• **Proposition 65**

• **Chemicals known to cause cancer:**

100-41-4	ethylbenzene
----------	--------------

• **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.	
------------------------------------	--

• **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.	
------------------------------------	--

• **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.	
------------------------------------	--

• **Carcinogenic categories**

• **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
-----------	--------	---

100-41-4	ethylbenzene	D
----------	--------------	---

• **TLV (Threshold Limit Value established by ACGIH)**

13463-67-7	titanium dioxide	A4
------------	------------------	----

1330-20-7	xylene	A4
-----------	--------	----

100-41-4	ethylbenzene	A3
----------	--------------	----

77-58-7	dibutyltin dilaurate	A4
---------	----------------------	----

7647-01-0	hydrogen chloride	A4
-----------	-------------------	----

• **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7	titanium dioxide
------------	------------------

• **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.	
------------------------------------	--

• **Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

• **Hazard symbols:**



Irritant

• **Risk phrases:**

Flammable.

Irritating to skin.

• **Safety phrases:**

Keep out of the reach of children.

Keep away from sources of ignition - No smoking.

If swallowed, seek medical advice immediately and show this container or label.

Dispose of this material and its container to hazardous or special waste collection point.

• **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• **Department issuing MSDS:** Product safety department

• **Contact:** Ms. Topaljikian