# 5 STAR XTREME AUTOBODY PRODUCTS TECHNICAL DATA INFORMATION

**DATED: AUGUST 2013** 

### **PRODUCT NUMBER**

#5902 - Final Wipe Wax and Grease Remover

### **DESCRIPTION**

#5902 FINAL WIPE WAX & GREASE REMOVER is a solvent blend surface cleaner formulated to remove wax, grease, silicone, oils and other contaminants from surfaces to be painted. This fast drying product leaves no residue making it the perfect pre-paint surface cleaner for any substrate.

### **DIRECTIONS FOR USE**

## PRODUCT MUST BE APPLIED WITH A PUMP SPRAYER TO BE COMPLIANT IN CANADA.

- #5902 should be used AFTER sanding a repair area prior to painting. For best performance, compressed air should be used to eliminate excess sanding dust from the repair area before using Final Wipe.
- 2. Apply a liberal amount of #5902 to a clean dry lint free cloth, saturating it. Have a second clean, dry cloth available before proceeding.
- 3. Wipe surface in one direction with saturated cloth. Clean 2 x 2 area at a time, changing cloths frequently to prevent surface contaminants.
- 4. Immediately wipe surface dry with a clean dry cloth while surface is still wet.
- 5. Remove excess #5902 with a clean cloth soaked in clean water. Wipe dry with a clean, dry cloth.

### **IMPORTANT:**

THIS PRODUCT IS DESIGNED TO BE USED AS A HAND-HELD SPRAY BOTTLE SPOT CLEANER USED TO PREPARE SURFACES PRIOR TO SANDING. WHEN USED AS SUCH, THIS PRODUCT IS EXCLUDED FROM COMPLIANCE WITH CANADIAN ENVIRONMENTAL PROTECTION ACT 1999 - VOLATILE ORGANIC COMPOUND (V0C) CONCENTRATION LIMITS FOR AUTOMOTIVE REFINISH PRODUCTS REGULATION.

DO NOT USE #5902 ON PLASTIC OR FIBERGLASS PARTS. APPLICATION ON THESE SURFACES CAN GENERATE STATIC BUILD-UP, WHICH CAN RESULT IN FLASH FIRE. DO NOT USE #5902 ON SOLUABLE MATERIALS, LIKE LACQUER PRIMERS OR TOPCOATS.

### **TECHNICAL DATA**

Color:

#5902 Water-White

VOC:

#5902 6.3 lbs gal (RTS)

NOTE: ABI products are not recommended for use in temperatures below 60° F. Use below these temperatures will effect dry times and performance.

### FOR INDUSTRY USE ONLY Read MSDS Before Use

The contents of the package must be blended with other components before the product can be used. Any mixture of components will have hazards of all components. Before opening the packages, read all warning labels. Follow all precautions. The material is designed for application only by professionally trained personnel using proper equipment under controlled conditions, and is not intended for sale to the general public.

SEE MSDS AND PRODUCT LABELS FOR ADDITIONAL SAFETY INFORMATION. Autobody Brands International a division of IAMG – International Autobody Marketing Group - www.autobodybrands.com