



5920

Premium Rubberized Undercoating

(16oz.)



5 STAR XTREME PREMIUM RUBBERIZED UNDERCOATING

A flexible, asphaltic coating which contains no asbestos fiber. It combines the flexibility and sealing properties of rubber, with superior coating capabilities. An effective textured coating that dries fast without thick peaks and thin pockets which tend to weaken the film and trap moisture. A durable protective coating that helps retard the effects of rust corrosion, moisture, fumes, dust, heat and cold. An excellent rust protective coating for autobody repair. Creates an effective sound barrier that reduces vibration and deadens sound in wheel wells, quarter panels, fenders, frames, under carriages, spot repairs and welded joints.

DIRECTIONS: (1) Shake well before using (min 3 minutes) making sure the agitator ball moves freely.

(2) Use at room temperature (70°F or 21°C) for best results.

(3) Use in a well ventilated area.

(4) Mask areas not to be undercoated from overspray or misdirected spray.

(5) Clean surfaces free of dirt, grease, oil, wax, rust, loose paint and dry surface thoroughly.

(6) Point opening of spray button toward object to be coated.

(7) Hold can upright 12-16 inches from object to be coated.

(8) Accidental overspray should be wiped off immediately with clear solvent.

(9) Clean spray button immediately by holding can upside down and spraying until clear gas appears (about 5 seconds).



Scan this **QR Code** with your **SMART PHONE** for instant **MSDS** and **TDS** information.
#5920



Call 1-87REFINISH (1-877-334-6474) to find your local 5 STAR XTREME Autobody Products supplier, or visit our website: www.5starxtreme.com - MSDS/TDS/High Resolution photos available ©2014 Part #5920