

**5 STAR XTREME AUTOBODY PRODUCTS**  
**TECHNICAL DATA INFORMATION**  
**DATED: DECEMBER 2013**

**PRODUCT NUMBER**

#5920 – Premium Rubberized Undercoating BLACK (Aerosol 16 oz.)

**DESCRIPTION:**

#5920 is a flexible, asphaltic coating which contains no asbestos fiber. It combines the flexibility and sealing properties of rubber, with superior coating capabilities. An effective textured coating that dries fast without thick peaks and thin pockets which tend to weaken the film and trap moisture. A durable protective coating that helps retard the effects of rust corrosion, moisture, fumes, dust, heat and cold. An excellent rust protective coating for autobody repair. Creates an effective sound barrier that reduces vibration and deadens sound in wheel wells, quarter panels, fenders, frames, under carriages, spot repairs and welded joints.

**DIRECTIONS:**

(1) Shake well before using (min. 3 minutes) making sure the agitator ball moves freely. (2) For best results, use at room temperature (70°F or 21°C). (3) Use in a well ventilated area. (4) Mask areas not to be undercoated from overspray or misdirected spray. (5) Clean surfaces free of dirt, grease, oil, wax, rust, loose paint, and dry surface thoroughly. (6) Point opening of spray button toward object to be coated. (7) Hold can upright 12-16 inches from object to be coated. (8) Accidental overspray should be wiped off immediately with clear solvent. (9) Clean spray button immediately by holding can upside down and spraying until clear gas appears (about 5 seconds).

**CAUTIONS:**

CAUTIONS CONTAINS ALIPHATIC HYDROCARBONS. Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively. Keep area ventilated during use and until all vapors are gone. DO NOT SMOKE - Extinguish all flames, pilot lights and heaters - Turn off stoves, electric tools and appliances, and any other sources of ignition. Avoid prolonged exposure to sunlight or heat from radiators, stoves, hot water and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120°F. Keep upright in a cool, dry place. Do not discard empty can in trash compactor. Use with adequate ventilation. Avoid continuous breathing of vapor and spray mist. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or wear respiratory protection (NIOSH approved) or leave the area. Avoid contact with eyes and skin. Wash hands after using. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call physician. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can

cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

**SEE MSDS AND PRODUCT LABELS FOR ADDITIONAL SAFETY INFORMATION.**

**ABI – Autobody Brands International a division of IAMG – International Autobody Marketing Group. [www.5starxtreme.com](http://www.5starxtreme.com) - Scottsdale, AZ 85257**