

## 5 STAR XTREME AUTOBODY PRODUCTS

### TECHNICAL DATA INFORMATION

**DATED: July 2017**

#### PRODUCT DESCRIPTION

#5961 PREMIUM ADHESION PROMOTER AEROSOL 15OZ.

#### DESCRIPTION:

5 STAR XTREME ADHESION PROMOTER is an all-purpose clear primer that improves adhesion of enamel and lacquer topcoats to nearly any surface, including most plastics and chrome. It is fast drying and provides superior adhesion on all flexible and rigid plastic parts. Features a sprayhead for spray gun-like application.

- Topcoat after 10 minutes
- Before 30 minutes for maximum adhesion

#### Suggested Uses:

Glass	Chrome	Ceramic/Tile
Vinyl	Bumpers	Fiberglass
Aluminum	Polypropylene	Polycarbonate
Molded Trim Pieces		

**CAUTION:** May attack some types of soft plastics.

#### INDUSTRIES:



#### DIRECTIONS:

(1.) Surface must be clean, dry and free of rust before painting. Protect surrounding areas from spray mist. For best results, use when can is between 50°F and 90°F (10°C and 32°C).

(2.) Shake can at least one minute after rattle is heard and occasionally during use.

(3.) Spray surface with steady even strokes at a distance of 8 to 10 inches (20 to 25cm). Several light coats give a better finish than one heavy coat.

(4.) If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. Do not stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.

(5.) To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. **DO NOT incinerate or compact. After each use, turn can upside down and spray several seconds to clear spray tip.**

## TYPICAL PROPERTIES:

Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.73
Solids Content	5%
VOC content	49%
HAPs Content	<1%
Shelf life	Guaranteed for 2 years
Prop 65 substances	No
Hazard Class	2.1
FOOD CONTACT RATING	NO
Shipping Classification Consumer Commodity ORM-D, UN 1950	

## CLEANUP:

Clean spray equipment with appropriate cleaning materials compliant with VOC regulations in your area.

## STORAGE:

AEROSOLS should be stored in a cool, dry place with adequate ventilation away from heat, sparks and flames. The shelf life for #5961 is 2 years when stored under normal conditions.

## DISCLAIMER:

The information supplied in this document is for guidance only and should not be construed as a warranty. All implied warranties are expressly disclaimed. All users of the materials are responsible for assuring that it is suitable for their needs, environment and use. All data subject to change as 5 STAR XTREME deems appropriate.

Users should review the Safety Data Sheet (SDS) and product label to determine possible health hazards, appropriate engineering controls and precautions to be observed in using the material.

## SAFETY INFORMATION - FOR INDUSTRY USE ONLY

**DANGER Extremely flammable aerosol.** Contains gas under pressure; may explode if heated. Causes skin irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

**Prevention:** Pressurized container: do not pierce or burn, even after use. Use only with adequate ventilation. Do not breathe dust/vapors/spray mist. Avoid contact with eyes/skin/clothing. Wear protective gloves/clothing/glasses. Keep away from heat/sparks/open flames/hot surfaces. Do not eat/drink/smoke when using this product. Do not spray on naked flame or other ignition sources.

**Response:** In case of fire, use extinguishing powder or water spray. Immediately contact a doctor or **POISON CONTROL CENTER** if you feel unwell. If medical attention is needed, have product label at hand. **IF IN EYES:** Rinse with water for several minutes. Remove contact lenses if present. If eye irritation persists seek medical attention. **IF SWALLOWED:** Rinse mouth with water. Do not induce vomiting. **IF INHALED:** Remove to fresh air. **IF ON SKIN:** Wash thoroughly with water. Remove all contaminated clothing. **Storage:** Store locked up. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. **Disposal:** Dispose of product in accordance with local/regional/national/international regulations. **Additional Precaution Statements:** Vapors may ignite explosively and cause a flash fire. Prevent buildup of vapors by opening windows and doors to achieve cross ventilation. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system

damage. Intentional misuse by deliberately inhaling the contents may be harmful or fatal. In cases where short and/or long term overexposure conditions exist, a charcoal filter respirator should be worn. Follow respirator manufacturer's directions for use.

**KEEP OUT OF REACH OF CHILDREN. READ ALL SDS BEFORE USE.**

**ABI- Autobody Brands International a division of IAMG - International Autobody Marketing Group - Scottsdale, AZ – [www.5starxtreme.com](http://www.5starxtreme.com)**

**1-87-REFINISH**