

5 STAR XTREME AUTOBODY PRODUCTS
TECHNICAL DATA INFORMATION
DATED: APRIL 2018

PRODUCT NUMBER

#5981 – Premium Superior Rubberized Undercoating (Aerosol 14.3 oz.)

VOC compliant

DESCRIPTION:

Superior Rubberized Undercoating is a premium quality paintable surface protectant designed for Automotive applications. High build, fast drying, paintable undercoating which contains no asphalt. Extremely durable with excellent corrosion protection. Will form a hard, textured finish that will help prevent chipping and abrasions caused by stones and debris while inhibiting development of rust. Easy to use in areas where there is overlap. Fast dry in 20 mins, paintable in as little as 45 minutes. Will not dull or brown, stays true black!

DIRECTIONS:

Shake well before using. Clean the surface with complaint 5 STAR XTREME Wax and Grease Remover to remove grease and wax. Prime the surface if required. Mask the areas not to be sprayed. Spray in short even strokes until the desired texture is obtained. Remove over-spray with Wax and Grease Remover. Allow to dry for 1 hour before painting. To clear the nozzle, invert the can and spray.

CAUTIONS:

WARNING! CONTENTS MAY CATCH FIRE. CONTENTS MAY BE HARMFUL IF INHALED. MAY IRRITATE EYES. MAY IRRITATE SKIN. CONTAINER MAY EXPLODE IF HEATED. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DROWSINESS, DIZZINESS, HEADACHE OR NAUSEA. MAY PRODUCE BIRTH DEFECTS IN THE DEVELOPING FETUS. POSSIBLE CANCER AGENT BASED ON TESTS WITH LABORATORY ANIMALS. Do not smoke. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Use only in a well-ventilated area. Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor. Do not swallow. Do not puncture. Do not burn. Store away from heat. Wear suitable protective clothing, gloves and eye protection. Wash hands thoroughly after handling.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID TREATMENT: Contains: Acetone, Toluene, Propane, Isobutane and Carbon Black. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes or on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person into fresh air.

WARNING: Cancer and Reproductive Harm
- www.P65Warnings.ca.gov.

FLAT COATINGS PWR (MIR) < 1.20

AEROSOL UNDERCOATING VOC < 40% w/w VOC COMPLIANT

SEE SDS AND PRODUCT LABELS FOR ADDITIONAL SAFETY INFORMATION.

For accident or chemical emergency call CHEMTREC

1-800-424-9300 (day or night).

Made Exclusively for ABI/Autobody Brands International

a division of IAMG/International Autobody Marketing Group Scottsdale, AZ 85257

www.5starxtreme.com

**ABI – Autobody Brands International a division of IAMG – International
Autobody Marketing Group. www.5starxtreme.com - Scottsdale, AZ 85257**

1-87-REFINISH