



# SAFETY DATA SHEET

Revision date 15-Jun-2017

Version 6

Supersedes Date: 06-Jun-2017

## Section 1: PRODUCT AND COMPANY IDENTIFICATION

**Product Name** ACRYLIC URETHANE SS - BRILLIAN  
**Product Code** AD-702.G01  
**UN/ID no** UN1263  
**Recommended Use** Paint, Coatings

### Details of the supplier of the safety data sheet

See section 16 for more information

ADVANTAGE REFINISH PRODUCTS  
a division of IAMG/International Autobody Marketing Group  
1505 N. Hayden Road  
Suite 111  
Scottsdale, AZ 85257  
www.AdvantageRefinish.com  
1-87REFINISH

ADVANTAGE REFINISH PRODUCTS  
a division of IAMG/International Autobody Marketing Group  
1368 United Blvd.  
Unit 102  
Coquitlam, BC V3K 6Y2  
www.AdvantageRefinish.com  
1-87REFINISH

**E-mail address** [No information available](#)

**Emergency telephone number** Chemtrec: 800-424-9300

## Section 2: HAZARDS IDENTIFICATION

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all the information required by the HPR

### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Flammable liquids	Category 2

### Label elements



Signal word

**DANGER**

#### HAZARD STATEMENTS

Highly flammable liquid and vapor  
Causes skin irritation  
Causes serious eye irritation  
May cause an allergic skin reaction  
Suspected of causing cancer  
Suspected of damaging fertility or the unborn child

#### PREVENTION

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### RESPONSE

IF exposed or concerned: Get medical advice/attention.

##### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

##### Skin

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

##### Inhalation

IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

##### Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

##### Fire

In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction.

#### STORAGE

Store locked up. Store in a well-ventilated place. Keep cool.

#### DISPOSAL

Dispose of contents/containers in accordance with local regulations.

#### OTHER HAZARDS

Not applicable.

#### UNKNOWN ACUTE TOXICITY

0% of the mixture consists of ingredient(s) of unknown toxicity.

### Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
Methyl acetate	79-20-9	15 - <20
Benzene, 1-chloro-4-(trifluoromethyl)-	98-56-6	5 - <10
Methyl propyl ketone	107-87-9	3 - <5
Methyl n-amyl ketone	110-43-0	3 - <5
Carbon black	1333-86-4	1 - <3
Solvent naphtha, petroleum, light aromatic	64742-95-6	1 - <3
n-Butyl acetate	123-86-4	1 - <3

Ethylene glycol monobutyl ether acetate	112-07-2	1 - <3
Zirconium ethyl hexoate	22464-99-9	0.3 - <1
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	0.3 - <1
Rutile (TiO <sub>2</sub> )	1317-80-2	0.3 - <1
Ethylbenzene	100-41-4	0.1 - <0.3
Decanedioic acid, 1-methyl 10-(1,2,2,6,6-pentamethyl-4-piperidiny) ester	82919-37-7	0.1 - <0.3
2-Butanone, oxime	96-29-7	0.1 - <0.3

## Section 4: FIRST AID MEASURES

### First Aid Measures

#### General advice

IF exposed or concerned: Get medical advice/attention

#### Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

#### Skin Contact

If skin irritation or rash occurs: Get medical advice/attention IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower Wash contaminated clothing before reuse

#### Inhalation

IF INHALED: Call a POISON CENTER or doctor if you feel unwell

#### Ingestion

Do NOT induce vomiting IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

### Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

## Section 5: FIRE FIGHTING MEASURES

**Flammable properties** Flammable liquid.

**flash point** 9 °F / -13 °C

**Upper flammability limit:** No information available

**Lower flammability limit:** No information available

**Autoignition temperature** No information available

#### Explosion data

Sensitivity to Mechanical Impact No information available.  
Sensitivity to Static Discharge No information available.

#### Suitable extinguishing media

Dry chemical, CO<sub>2</sub>, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

**Hazardous combustion products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>).

**Specific hazards arising from the chemical**

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact.

**Special protective equipment for fire-fighters**

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

**Section 6: ACCIDENTAL RELEASE MEASURES****Personal precautions**

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

**Environmental precautions**

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

**Methods for containment**

Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up**

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

**Section 7: HANDLING AND STORAGE****Advice on safe handling**

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

**General Hygiene Considerations**

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

**Storage Conditions**

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

**Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****Exposure Guidelines****Exposure Limits**

If S\* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	Alberta	British Columbia	Ontario TWA	Quebec	OSHA PEL
Methyl acetate 79-20-9	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 606 mg/m <sup>3</sup> STEL: 250 ppm STEL: 757 mg/m <sup>3</sup>	TWA: 200 ppm STEL: 250 ppm	TWA: 200 ppm STEL: 250 ppm	TWA: 200 ppm TWA: 606 mg/m <sup>3</sup> STEL: 250 ppm STEL: 757 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 610 mg/m <sup>3</sup>
Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup>	TWA: 2.5 mg/m <sup>3</sup> F TWA: 2.5 mg/m <sup>3</sup> dust

Methyl propyl ketone 107-87-9	STEL: 150 ppm	TWA: 200 ppm TWA: 705 mg/m <sup>3</sup> STEL: 250 ppm STEL: 881 mg/m <sup>3</sup>	TWA: 150 ppm STEL: 250 ppm	STEL: 150 ppm	TWA: 150 ppm TWA: 530 mg/m <sup>3</sup>	TWA: 200 ppm TWA: 700 mg/m <sup>3</sup>
Methyl n-amyl ketone 110-43-0	TWA: 50 ppm	TWA: 50 ppm TWA: 233 mg/m <sup>3</sup>	TWA: 50 ppm	TWA: 25 ppm TWA: 115 mg/m <sup>3</sup>	TWA: 50 ppm TWA: 233 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>
Carbon black 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable fraction	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup>
n-Butyl acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 713 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>	TWA: 20 ppm	TWA: 150 ppm STEL: 200 ppm	TWA: 150 ppm TWA: 713 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup>
Ethylene glycol monobutyl ether acetate 112-07-2	TWA: 20 ppm	TWA: 20 ppm TWA: 131 mg/m <sup>3</sup>	TWA: 20 ppm	TWA: 20 ppm		
Zirconium ethyl hexoate 22464-99-9	STEL: 10 mg/m <sup>3</sup> Zr TWA: 5 mg/m <sup>3</sup> Zr	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> Zr
Rutile (TiO <sub>2</sub> ) 1317-80-2	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 125 ppm STEL: 543 mg/m <sup>3</sup>	TWA: 20 ppm	TWA: 20 ppm	TWA: 100 ppm TWA: 434 mg/m <sup>3</sup> STEL: 125 ppm STEL: 543 mg/m <sup>3</sup>	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>

### Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

### Personal Protective Equipment

#### Eye/face protection

Tight sealing safety goggles.

#### Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

#### Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing. Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber.

#### Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

#### Thermal Protection

No information available

### Environmental exposure controls

Do not allow into any sewer, on the ground or into any body of water. Local authorities should be advised if significant spillages cannot be contained.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Physical state	liquid
Appearance	No information available
Odor	Solvent
Color	black
Odor Threshold	No information available
pH value	No information available
Melting point/freezing point	No information available
Boiling point / boiling range	57 °C / 135 °F
flash point	-13 °C / 9 °F
evaporation rate	No information available

<b>Flammability (solid, gas)</b>	No information available
<b>Flammability Limit in Air</b>	
<b>Upper flammability limit:</b>	No information available
<b>Lower flammability limit:</b>	No information available
<b>Vapor Pressure</b>	No information available
<b>vapor density</b>	No information available
<b>Density (lbs per US gallon)</b>	8.59
<b>specific gravity</b>	1.03
<b>Solubility(ies)</b>	No information available
<b>Partition coefficient</b>	No information available
<b>Autoignition temperature</b>	No information available
<b>Decomposition temperature</b>	No information available
<b>Kinematic viscosity</b>	No information available
<b>Dynamic viscosity</b>	No information available

#### Other information

### Section 10: STABILITY AND REACTIVITY

<b>Stability</b>	Stable under normal conditions.
<b>Incompatible materials</b>	Strong bases. Strong oxidizing agents.
<b>Conditions to avoid</b>	Heat, flames and sparks.
<b>Hazardous Decomposition Products</b>	Carbon monoxide. Carbon dioxide (CO <sub>2</sub> ). Hydrocarbons. Chlorine.
<b>Possibility of Hazardous Reactions</b>	None under normal processing.
<b>Hazardous polymerization</b>	None under normal processing.

### Section 11: TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

##### **Eye contact**

Causes serious eye irritation

##### **Skin Contact**

Causes skin irritation

May cause an allergic skin reaction

##### **Ingestion**

Not applicable

##### **Inhalation**

Not applicable

#### Numerical measures of toxicity - Component Information

<b>Chemical Name</b>	<b>Oral LD50</b>	<b>Dermal LD50</b>	<b>Inhalation LC50</b>
Methyl acetate 79-20-9	> 5 g/kg ( Rat )	> 5 g/kg ( Rabbit )	= 16000 ppm ( Rat ) 4 h
Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6	= 13 g/kg ( Rat )	> 2 mL/kg ( Rabbit )	= 33 mg/L ( Rat ) 4 h
Methyl propyl ketone 107-87-9	= 1600 mg/kg ( Rat )	= 6480 mg/kg ( Rat ) = 6500 mg/kg ( Rabbit )	= 2000 ppm ( Rat ) 4 h
Methyl n-amyl ketone 110-43-0	= 1670 mg/kg ( Rat ) = 1600 mg/kg ( Rat )	= 12600 µL/kg ( Rabbit ) = 12.6 mL/kg ( Rabbit )	> 2000 ppm ( Rat ) 4 h
Carbon black 1333-86-4	> 15400 mg/kg ( Rat )	> 3 g/kg ( Rabbit )	-
Solvent naphtha, petroleum, light aromatic 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
n-Butyl acetate 123-86-4	= 10768 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 390 ppm ( Rat ) 4 h

Ethylene glycol monobutyl ether acetate 112-07-2	= 2400 mg/kg ( Rat )	= 1480 mg/kg ( Rabbit )	-
Zirconium ethyl hexoate 22464-99-9	-	-	-
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate 41556-26-7	= 2615 mg/kg ( Rat )	-	-
Rutile (TiO <sub>2</sub> ) 1317-80-2	> 10000 mg/kg ( Rat )	-	-
Ethylbenzene 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h
Decanedioic acid, 1-methyl 10-(1,2,2,6,6-pentamethyl-4-piperidyl) ester 82919-37-7	-	-	-
2-Butanone, oxime 96-29-7	= 930 mg/kg ( Rat )	1000 - 1800 mg/kg ( Rabbit )	> 4800 mg/m <sup>3</sup> ( Rat ) 4 h

#### **Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document .

<b>ATEmix (oral)</b>	5868 Mg/kg
<b>ATEmix (dermal)</b>	108931 Mg/kg
<b>ATEmix (inhalation-dust/mist)</b>	32.7 mg/l
<b>ATEmix (inhalation-vapor)</b>	240 mg/l

**UNKNOWN ACUTE TOXICITY** 0% of the mixture consists of ingredient(s) of unknown toxicity.

#### **Delayed and immediate effects as well as chronic effects from short and long-term exposure**

##### **Carcinogenicity**

According to IARC, Volume 93, no significant exposure to primary particles of titanium dioxide is thought to occur from use in paints since the pigment is bound to other materials. According to IARC, Volume 93, no significant exposure to primary particles of carbon black is thought to occur from use in paints since the pigment is bound to other materials.

<b>Chemical Name</b>	<b>ACGIH</b>	<b>IARC</b>	<b>NTP</b>	<b>OSHA</b>
Carbon black 1333-86-4	A3	Group 2B		X
Ethylene glycol monobutyl ether acetate 112-07-2	A3			
Rutile (TiO <sub>2</sub> ) 1317-80-2		Group 2B		X
Ethylbenzene 100-41-4	A3	Group 2B		X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen.

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present.

<b>Skin corrosion/irritation</b>	Causes skin irritation
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation
<b>Skin sensitization</b>	May cause an allergic skin reaction
<b>Respiratory sensitization</b>	Not applicable
<b>Germ cell mutagenicity</b>	Not applicable
<b>Carcinogenicity</b>	Suspected of causing cancer
<b>Reproductive Toxicity</b>	Suspected of damaging fertility or the unborn child
<b>Specific target organ toxicity (single exposure)</b>	Not applicable
<b>Specific target organ toxicity (repeated exposure)</b>	Not applicable
<b>Aspiration hazard</b>	Not applicable

## Section 12: ECOLOGICAL INFORMATION

### Ecotoxicity

Environmental precautions Prevent product from entering drains.

### Persistence and degradability

No information available

### Bioaccumulation

No information available

### Mobility

No information available

### Other adverse effects

No information available

## Section 13: DISPOSAL CONSIDERATIONS

**Waste from residues/unused products** Disposal should be in accordance with applicable regional, national and local laws and regulations

**Contaminated packaging** Improper disposal or reuse of this container may be dangerous and illegal.

## Section 14: TRANSPORT INFORMATION

	<u>TDG</u>	<u>IMDG</u>	<u>IATA</u>
UN/ID no	UN1263	UN1263	UN1263
Proper shipping name	Paint	Paint	Paint
Hazard Class	3	3	3
Packing Group	II	II	II
Environmental hazard	Not applicable		
Special Provisions		163, 367 EmS-No F-E, S-E	A3, A72, A192

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

*The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.*

## Section 15: REGULATORY INFORMATION

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory All components are listed or exempt from listing

**DSL** - Canadian Domestic Substances List Not all components are listed or exempt from listing

Chemical Name	Canada - NPRI (National Pollutant Release Inventory)
Methyl acetate	Part 4 Substance (as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999)
Benzene, 1-chloro-4-(trifluoromethyl)-	Part 4 Substance (as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999)
Methyl propyl ketone	Part 4 Substance (as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999)
Methyl n-amyl ketone	Part 4 Substance (as set out in Section 65 of the List of Toxic Substances in Schedule 1 of the Canadian Environmental Protection Act, 1999)
Solvent naphtha, petroleum, light aromatic	Part 5, Other Groups and Mixtures
n-Butyl acetate	Part 5, Individual Substances
Ethylene glycol monobutyl ether acetate	Part 5, Other Groups and Mixtures
Ethylbenzene	Part 1, Group A Substance



## Section 16: OTHER INFORMATION

### HMIS

Health hazards 2\*

\* = Chronic Health Hazard

Flammability 3

Physical hazards 0

Personal Protection X

Prepared By Regulatory Department

Revision date 15-Jun-2017

Revision Note No information available

### Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

**End of Safety Data Sheet**