



SAFETY DATA SHEET

Revision date 08-May-2020

Version 18

Supersedes Date: 24-Jan-2020

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Code AD-708.G01

Product Name ACRYLIC URETHANE SS - CHARCOAL

Other means of identification

No information available

Recommended use of the chemical and restrictions on use

Paint, Coatings

Details of the supplier of the safety data sheet

See section 16 for more
information

ADVANTAGE REFINISH PRODUCTS
a division of IAMG/International Autobody Marketing Group
1505 N. Hayden Road
Suite 111
Scottsdale, AZ 85257
www.AdvantageRefinish.com
1-87REFINISH

E-mail address [No information available](#)

Emergency telephone number

United States of America Chemtrec: 800-424-9300

Section 2: HAZARDS IDENTIFICATION

Classification

| | |
|-----------------------------------|------------|
| Skin corrosion/irritation | Category 2 |
| Serious eye damage/eye irritation | Category 2 |
| Skin sensitization | Category 1 |
| Carcinogenicity | Category 2 |
| Reproductive toxicity | Category 2 |
| Flammable liquids | Category 2 |

Label elements



Signal word

DANGER

HAZARD STATEMENTS

Highly flammable liquid and vapor
Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
Suspected of causing cancer
Suspected of damaging fertility or the unborn child

PREVENTION

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

RESPONSE

IF exposed or concerned: Get medical advice/attention.

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction.

STORAGE

Store locked up. Store in a well-ventilated place. Keep cool.

DISPOSAL

Dispose of contents/containers in accordance with local regulations.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

No information available.

OTHER HAZARDS

Not applicable.

UNKNOWN ACUTE TOXICITY .0002% of the mixture consists of ingredient(s) of unknown toxicity.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS No | weight-% |
|---------------|--------|----------|
|---------------|--------|----------|

| | | |
|--|-------------|-----------|
| Methyl acetate | 79-20-9 | 10 - 25 |
| Methyl n-amyl ketone | 110-43-0 | 10 - 25 |
| Benzene, 1-chloro-4-(trifluoromethyl)- | 98-56-6 | 5 - 10 |
| Methyl propyl ketone | 107-87-9 | 5 - 10 |
| Solvent naphtha, petroleum, light aromatic | 64742-95-6 | 1 - 3 |
| Zirconium ethyl hexoate | 22464-99-9 | 0.3 - 1 |
| Proprietary additive | Proprietary | 0.3 - 1 |
| Carbon black | 1333-86-4 | 0.3 - 1 |
| Ethylbenzene | 100-41-4 | 0.1 - 0.3 |
| Alkanoate ester | Proprietary | 0.1 - 0.3 |
| 2-Butanone, oxime | 96-29-7 | 0.1 - 0.3 |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4: FIRST AID MEASURES

First Aid Measures

General advice

IF exposed or concerned: Get medical advice/attention.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact

If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

Inhalation

IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

Ingestion

Do NOT induce vomiting. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, CO₂, water spray or alcohol-resistant foam.

Not to be used for safety reasons:

Strong water jet

Specific hazards arising from the chemical

Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact.

Special protective equipment for fire-fighters

Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

For emergency responders

Use personal protection recommended in Section 8.

Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

Section 7: HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

General Hygiene Considerations

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

Incompatible materials

Strong bases. Strong oxidizing agents. Amines.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits

If S* appears in the OEL table, it indicates this chemical contains a skin notation.

| Chemical Name | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|---------------------------|-------------------------------|--|--|
| Methyl acetate 79-20-9 | STEL: 250 ppm TWA: 200 ppm | TWA: 200 ppm TWA: 610 mg/m ³ | IDLH: 3100 ppm TWA: 200 ppm TWA: 610 mg/m ³ STEL: 250 ppm STEL: 760 mg/m ³ |

| | | | |
|--|--|--|---|
| Methyl n-amyl ketone 110-43-0 | TWA: 50 ppm | TWA: 100 ppm TWA: 465 mg/m ³ | IDLH: 800 ppm TWA: 100 ppm TWA: 465 mg/m ³ |
| Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6 | TWA: 2.5 mg/m ³ F | TWA: 2.5 mg/m ³ F | |
| Methyl propyl ketone 107-87-9 | STEL: 150 ppm | TWA: 200 ppm TWA: 700 mg/m ³ | IDLH: 1500 ppm TWA: 150 ppm TWA: 530 mg/m ³ |
| Zirconium ethyl hexoate 22464-99-9 | STEL: 10 mg/m ³ Zr TWA: 5 mg/m ³ Zr | TWA: 5 mg/m ³ Zr | IDLH: 25 mg/m ³ Zr TWA: 5 mg/m ³ except Zirconium tetrachloride Zr STEL: 10 mg/m ³ Zr |
| Carbon black 1333-86-4 | TWA: 3 mg/m ³ inhalable particulate matter | TWA: 3.5 mg/m ³ | IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH |
| Ethylbenzene 100-41-4 | TWA: 20 ppm | TWA: 100 ppm TWA: 435 mg/m ³ | IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³ |

Appropriate engineering controls

Engineering Controls

Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles.

Skin and body protection

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing. Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber.

Hand Protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

Respiratory protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal Protection

No information available

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | |
|--------------------------------------|--------------------------|
| Physical state | liquid |
| Appearance | No information available |
| Odor | Solvent |
| Color | Silver |
| Odor Threshold | No information available |
| pH value | No information available |
| Melting point/freezing point | No information available |
| Boiling point / boiling range | 57 °C / 135 °F |
| flash point | -13 °C / 9 °F |

| | |
|-----------------------------|--------------------------|
| evaporation rate | No information available |
| Flammability (solid, gas) | No information available |
| Flammability Limit in Air | |
| Upper flammability limit: | No information available |
| Lower flammability limit: | No information available |
| Vapor Pressure | No information available |
| vapor density | No information available |
| Density (lbs per US gallon) | 8.46 |
| specific gravity | 1.01 |
| Solubility(ies) | No information available |
| Partition coefficient | No information available |
| Autoignition temperature | No information available |
| Decomposition temperature | No information available |
| Kinematic viscosity | No information available |
| Dynamic viscosity | No information available |

Other information

Section 10: STABILITY AND REACTIVITY

| | |
|------------------------------------|---|
| Reactivity | No information available. |
| Chemical stability | Stable under normal conditions. |
| Possibility of Hazardous Reactions | None under normal processing. |
| Hazardous polymerization | None under normal processing. |
| Conditions to avoid | Heat, flames and sparks. |
| Incompatible materials | Strong bases. Strong oxidizing agents. Amines. |
| Hazardous Decomposition Products | Carbon monoxide. Carbon dioxide (CO ₂). Hydrocarbons. Chlorine. |

Section 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact

Causes serious eye irritation

Skin Contact

May cause an allergic skin reaction

Causes skin irritation

Ingestion

Not applicable

Inhalation

Not applicable

Numerical measures of toxicity - Component Information

| Chemical Name | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|---|---|--|-----------------------------|
| Methyl acetate 79-20-9 | > 5 g/kg (Rat) | > 5 g/kg (Rabbit) | = 16000 ppm (Rat) 4 h |
| Methyl n-amyl ketone 110-43-0 | = 1600 mg/kg (Rat) = 1670 mg/kg (Rat) | = 12600 µL/kg (Rabbit) = 12.6 mL/kg (Rabbit) | 2000 - 4000 ppm (Rat) 6 h |
| Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6 | = 13 g/kg (Rat) | > 2 mL/kg (Rabbit) | = 33 mg/L (Rat) 4 h |
| Methyl propyl ketone 107-87-9 | = 1600 mg/kg (Rat) | = 6500 mg/kg (Rabbit) = 6480 mg/kg (Rat) | 2000 - 4000 ppm (Rat) 4 h |
| Solvent naphtha, petroleum, light aromatic 64742-95-6 | = 8400 mg/kg (Rat) | > 2000 mg/kg (Rabbit) | = 3400 ppm (Rat) 4 h |
| Zirconium ethyl hexoate | - | - | - |

| | | | |
|------------------------------|-----------------------|------------------------------|--------------------------------------|
| 22464-99-9 | | | |
| Proprietary additive | = 2615 mg/kg (Rat) | - | - |
| Carbon black 1333-86-4 | > 15400 mg/kg (Rat) | > 3 g/kg (Rabbit) | - |
| Ethylbenzene 100-41-4 | = 3500 mg/kg (Rat) | = 15400 mg/kg (Rabbit) | = 17.4 mg/L (Rat) 4 h |
| Alkanoate ester | - | - | - |
| 2-Butanone, oxime 96-29-7 | = 930 mg/kg (Rat) | 1000 - 1800 mg/kg (Rabbit) | > 4800 mg/m ³ (Rat) 4 h |

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

| | |
|--------------------------------------|------------|
| ATEmix (oral) | 3215 Mg/kg |
| ATEmix (inhalation-dust/mist) | 14.5 mg/l |
| ATEmix (inhalation-vapor) | 107 mg/l |

UNKNOWN ACUTE TOXICITY .0002% of the mixture consists of ingredient(s) of unknown toxicity.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity

According to IARC, Volume 93, no significant exposure to primary particles of titanium dioxide is thought to occur from use in paints since the pigment is bound to other materials. According to IARC, Volume 93, no significant exposure to primary particles of carbon black is thought to occur from use in paints since the pigment is bound to other materials.

| Chemical Name | ACGIH | IARC | NTP | OSHA |
|---------------------------|--------------|-------------|------------|-------------|
| Carbon black 1333-86-4 | A3 | Group 2B | | X |
| Ethylbenzene 100-41-4 | A3 | Group 2B | | X |

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen.

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present.

Skin corrosion/irritation Causes skin irritation

Serious eye damage/eye irritation Causes serious eye irritation

Skin sensitization May cause an allergic skin reaction

Respiratory sensitization Not applicable

Germ cell mutagenicity Not applicable

Carcinogenicity Suspected of causing cancer

Reproductive Toxicity Suspected of damaging fertility or the unborn child

Specific target organ toxicity (single exposure) Not applicable

Specific target organ toxicity (repeated exposure) Not applicable

Aspiration hazard Not applicable

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity

Environmental precautions Prevent product from entering drains.

Persistence and degradability

No information available

Bioaccumulation

No information available

Mobility

No information available

Other adverse effects

No information available

Section 13: DISPOSAL CONSIDERATIONS**Waste treatment methods****Disposal of wastes**

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging

Improper disposal or reuse of this container may be dangerous and illegal. Empty containers must be scrapped or reconditioned.

Section 14: TRANSPORT INFORMATION

| | | | |
|--|--|---------------------------------------|-----------------------|
| 14.1 UN/ID no | DOT UN1263 | IMDG UN1263 | IATA UN1263 |
| 14.2 Proper shipping name | Paint | Paint | Paint |
| 14.3 Hazard Class | 3 | 3 | 3 |
| 14.4 Packing Group | II | II | II |
| 14.5 Environmental hazard | | | |
| 14.6 Special Provisions | 149, B52, IB2, T4, TP1, TP8, TP28, 367 | 163, 367 EmS-No F-E, S-E | A3, A72, A192 |
| 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | No information available | | |

The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

Section 15: REGULATORY INFORMATION**International Inventories****TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

All components are listed or exempt from listing. (Active List).

DSL - Canadian Domestic Substances List

Not all components are listed or exempt from listing

US Federal Regulations

| Chemical Name | TSCA - Toxic Substances Control Act, Section 12(b) Export Notification |
|---|--|
| Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6 | Section 4 |

| Chemical Name | SARA 313 - Threshold Values % | Metals | Hazardous air pollutants (HAPs) content |
|---------------------------------------|----------------------------------|----------|--|
| Aluminum 7429-90-5 1 - 3 | 1 | Aluminum | |
| Ethylbenzene 100-41-4 0.1 - 0.3 | 0.1 | | Present |

| Chemical Name | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous Substances |
|--------------------------|-----------------------------|------------------------|---------------------------|----------------------------|
| Ethylbenzene 100-41-4 | 1000 lb | X | X | X |

| Chemical Name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ) |
|---------------|--------------------------|----------------|--------------------------|
| Ethylbenzene | 1000 lb | | RQ 1000 lb final RQ |

| | | | |
|----------|--|--|--------------------|
| 100-41-4 | | | RQ 454 kg final RQ |
|----------|--|--|--------------------|

US State Regulations

Rule 66 status of product

Not photochemically reactive.

California Proposition 65

WARNING: This product contains chemicals known to the State of California to cause cancer.

U.S. EPA Label information

EPA Pesticide registration number Not applicable

U.S. State Right-to-Know Regulations

| |
|--|
| Chemical Name |
| Proprietary Non-Hazardous Ingredient - Proprietary CAS |
| Methyl acetate 79-20-9 |
| Methyl n-amyl ketone 110-43-0 |
| Benzene, 1-chloro-4-(trifluoromethyl)- 98-56-6 |
| Methyl propyl ketone 107-87-9 |
| Proprietary Non-Hazardous Ingredient - Proprietary CAS |
| Aluminum 7429-90-5 |
| Solvent naphtha, petroleum, light aromatic 64742-95-6 |
| Zirconium ethyl hexoate 22464-99-9 |
| Ethylbenzene 100-41-4 |
| 2-Butanone, oxime 96-29-7 |

Section 16: OTHER INFORMATION

HMIS

Health hazards 2*

* = Chronic Health Hazard

Flammability 3

Physical hazards 1

Personal Protection X

Prepared By Regulatory Department

Revision date 08-May-2020

Revision Note No information available

Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A

PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

End of Safety Data Sheet